

Title (en)
Droplet ejecting head and printing apparatus

Title (de)
Tropfenausgabekopf und Druckvorrichtung

Title (fr)
Tête d'éjection de gouttelettes et dispositif d'impression

Publication
EP 2599633 B1 20151021 (EN)

Application
EP 12194830 A 20121129

Priority
JP 2011264097 A 20111201

Abstract (en)
[origin: EP2599633A1] A droplet ejecting head is described and comprises an actuator in which multiple ink flow channels (18) and multiple partition walls (17) are alternatively arranged. The partition wall responds to an applied voltage given to an electrode formed on a surface of the partition wall and does deformation motion by which the ink in the ink flow channel is ejected from a nozzle. The ink flow channel has a rectangular cross section and an aspect ratio (vertical length h/ horizontal length w) of the cross sectional shape of the ink flow channel is 5.00 or more and less than 7.75, and a resonance frequency of the partition wall is 1.5 MHz or more.

IPC 8 full level
B41J 2/14 (2006.01)

CPC (source: EP)
B41J 2/14209 (2013.01); **B41J 2202/11** (2013.01)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2599633 A1 20130605; EP 2599633 B1 20151021; CN 103129142 A 20130605; CN 103129142 B 20150325; JP 2013116571 A 20130613; JP 5919775 B2 20160518

DOCDB simple family (application)
EP 12194830 A 20121129; CN 201210502013 A 20121130; JP 2011264097 A 20111201