

Title (en)
STEERING DEVICE

Title (de)
LENKVORRICHTUNG

Title (fr)
DISPOSITIF DE DIRECTION

Publication
EP 2607184 B1 20150909 (EN)

Application
EP 11790846 A 20110713

Priority
• JP 2010184972 A 20100820
• JP 2011065940 W 20110713

Abstract (en)
[origin: EP2607184A1] In a steering device having a steering lock device, stress applied to a base portion of a flange section is reduced. The relief portions (47) and (48) have round corners (471) and (481) formed where the relief portions (47) and (48) meet the outer periphery of the outer column (4), respectively. With the relief portions (47) and (48) concave by ≈ 3 from the mounting surface (445), radius R1 of each of the round corners (471) and (481) of the relief portions (47) and (48) can be made larger than radius R2 of a round corner (447) of the mounting surface (445). This makes it possible to avoid interference between the relief portions (47) and (48) and the corner (631) at an inner end, in the vehicle width direction, of the right clamping surface (63) of the steering lock device (6).

IPC 8 full level
B60R 25/02 (2013.01); **B60R 25/021** (2013.01)

CPC (source: EP US)
B60R 25/0211 (2013.01 - EP US); **B60R 25/02115** (2013.01 - US); **Y10T 70/5655** (2015.04 - EP US); **Y10T 70/5659** (2015.04 - EP US); **Y10T 70/5956** (2015.04 - EP US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2607184 A1 20130626; EP 2607184 A4 20140723; EP 2607184 B1 20150909; CN 102448781 A 20120509; CN 102448781 B 20140108; JP 2012040983 A 20120301; JP 5360017 B2 20131204; US 2013180297 A1 20130718; US 8955361 B2 20150217; WO 2012023365 A1 20120223

DOCDB simple family (application)
EP 11790846 A 20110713; CN 201180001068 A 20110713; JP 2010184972 A 20100820; JP 2011065940 W 20110713; US 201113376981 A 20110713