

Title (en)
MULTILAYER THERMOPLASTIC SEMI-FINISHED FIBER MATRIX PRODUCT

Title (de)
MEHRSCHICHTIGES THERMOPLASTISCHES FASER-MATRIX-HALBZEUG

Title (fr)
SEMI-PRODUIT À MATRICE DE FIBRES THERMOPLASTIQUE MULTICOUCHE

Publication
EP 2625038 A1 20130814 (DE)

Application
EP 11767437 A 20111007

Priority
• EP 10187010 A 20101008
• EP 2011067593 W 20111007
• EP 11767437 A 20111007

Abstract (en)
[origin: EP2439068A1] The multilayer thermoplastic of a sandwich construction made of a semifinished sheet comprises a core layer having a thickness of 0.3-5 mm of continuous endless fiber reinforced thermoplastic composite materials or of long fiber reinforced thermoplastic composite materials, and a thermoformable thermoplastic molding material layer having a thickness of 0.1-3 mm. An entire surface of the upper- and/or under-side is connected with the thermoformable thermoplastic molding material layer. The core layer contains a reinforcement fiber of 0.001-80 wt.% and has a fiber diameter of 3-40 μ m. The multilayer thermoplastic of a sandwich construction made of a semifinished sheet comprises a core layer having a thickness of 0.3-5 mm of continuous endless fiber reinforced thermoplastic composite materials or of long fiber reinforced thermoplastic composite materials, and a thermoformable thermoplastic molding material layer having a thickness of 0.1-3 mm. An entire surface of the upper- and/or under-side is connected with the thermoformable thermoplastic molding material layer. The core layer contains a reinforcement fiber of 0.001-80 wt.% and has a fiber diameter of 3-40 μ m. The core layer and the material layer are connected by bonding, welding, laminating, coating and calendering. The molding material layer is applied on the core layer by coating processes. The thermoformable thermoplastic molding material layer has a comparable or higher melting point than the matrix of the fiber reinforced thermoplastic composite materials in the core layer and a temperature of shear rates of 1/s-100/s. An independent claim is included for a method for producing multilayer thermoplastic of a sandwich construction made of a semifinished sheet.

IPC 8 full level
B32B 27/34 (2006.01)

CPC (source: EP KR)
B29C 70/086 (2013.01 - EP); **B29C 70/16** (2013.01 - EP); **B29C 70/465** (2013.01 - EP); **B32B 5/022** (2013.01 - EP);
B32B 5/22 (2013.01 - EP); **B32B 5/26** (2013.01 - EP); **B32B 5/28** (2013.01 - EP KR); **B32B 27/00** (2013.01 - EP); **B32B 27/04** (2013.01 - KR);
B32B 27/34 (2013.01 - EP KR); **B32B 27/36** (2013.01 - EP); **B32B 2250/40** (2013.01 - EP); **B32B 2260/046** (2013.01 - EP);
B32B 2262/101 (2013.01 - EP); **B32B 2262/106** (2013.01 - EP); **B32B 2605/00** (2013.01 - EP); **B32B 2607/00** (2013.01 - EP);
Y02P 70/50 (2015.11 - EP)

Citation (search report)
See references of WO 2012045878A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2439068 A1 20120411; BR 112013008204 A2 20190924; CN 103221216 A 20130724; CN 103221216 B 20151014;
EP 2625038 A1 20130814; EP 2650126 A1 20131016; JP 2013544669 A 20131219; KR 20130097218 A 20130902;
WO 2012045878 A1 20120412

DOCDB simple family (application)
EP 10187010 A 20101008; BR 112013008204 A 20111007; CN 201180052355 A 20111007; EP 11767437 A 20111007;
EP 13176348 A 20111007; EP 2011067593 W 20111007; JP 2013532225 A 20111007; KR 20137011807 A 20111007