

Title (en)  
Locking cylinder

Title (de)  
Schliesszylinder

Title (fr)  
Cylindre de fermeture

Publication  
**EP 2628874 A3 20180124 (DE)**

Application  
**EP 13154438 A 20130207**

Priority  
DE 102012003168 A 20120217

Abstract (en)  
[origin: EP2628874A2] The lock cylinder has two housing portions (12) which are interconnected with variable spacing by an elongated coupling element (14). The coupling element is retained in receptacles of the housing portions along the longitudinal axis of the lock cylinder. The coupling element is adjustable between locking position in which the coupling element is axially locked in the receptacles, and an adjustment position in which the coupling element is axially slidably received in the receptacles by rotation about the longitudinal axis.

IPC 8 full level  
**E05B 9/04** (2006.01); **E05B 9/10** (2006.01)

CPC (source: EP)  
**E05B 9/045** (2013.01); **E05B 2009/046** (2013.01)

Citation (search report)

- [A] AT 394605 B 19920525 - EMSENHUBER ANTON [AT]
- [A] DE 20103456 U1 20010613
- [AD] EP 1802831 B1 20091216 - ABUS PFAFFENHAIN GMBH [DE]
- [A] EP 2410110 A2 20120125 - DOM SICHERHEITSTECHNIK [DE]

Cited by  
CN105239840A; CN103774920A; CN114856324A; CN111997443A; EP3109383A1; ITUB20160673A1; CN108779650A; EP3348751A1; WO2017137341A1; US10801233B2; US11808066B2

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**EP 2628874 A2 20130821; EP 2628874 A3 20180124; EP 2628874 B1 20180912;** DE 102012003168 A1 20130822; DK 2628874 T3 20181112; ES 2701757 T3 20190225

DOCDB simple family (application)  
**EP 13154438 A 20130207;** DE 102012003168 A 20120217; DK 13154438 T 20130207; ES 13154438 T 20130207