

Title (en)

Wire electrical discharge method for reducing machining damage during cutting machining and escape machining

Title (de)

Drahterodierverfahren zur Reduzierung von Bearbeitungsschäden während der Schneid- und Austrittsbearbeitung

Title (fr)

Procédé de décharge électrique à fil pour la réduction de dommages d'usinage pendant l'usinage de découpe et usinage d'évacuation

Publication

EP 2631029 B1 20190327 (EN)

Application

EP 12195613 A 20121205

Priority

JP 2012040461 A 20120227

Abstract (en)

[origin: EP2631029A2] A wire electrical discharge machine includes an approach control unit. The approach control unit relatively moves a wire electrode with respect to a workpiece while inclining the wire electrode within a plane parallel to the machining surface to which the wire electrode approaches, in an approach section where the wire electrode performs cutting machining on the machining surface of the workpiece.

IPC 8 full level

B23H 7/06 (2006.01); **B23H 7/20** (2006.01); **B23H 9/12** (2006.01)

CPC (source: EP US)

B23H 1/02 (2013.01 - US); **B23H 7/065** (2013.01 - EP US); **B23H 7/20** (2013.01 - EP US); **B23H 9/12** (2013.01 - EP US); **G05B 2219/45221** (2013.01 - US)

Citation (examination)

US 4820894 A 19890411 - FRANCOIS CORCELLE [FR], et al

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2631029 A2 20130828; **EP 2631029 A3 20141105**; **EP 2631029 B1 20190327**; CN 103286397 A 20130911; CN 103286397 B 20150527; JP 2013173212 A 20130905; JP 5369205 B2 20131218; US 2013220979 A1 20130829; US 9085037 B2 20150721

DOCDB simple family (application)

EP 12195613 A 20121205; CN 201310061938 A 20130227; JP 2012040461 A 20120227; US 201213688478 A 20121129