

Title (en)

A method of coating an end cap of a fragment retention lamp, apparatus therefor, and lamp manufactured thereby

Title (de)

Verfahren zur Abdeckung des Sockels einer splittergeschützten Lampe, Vorrichtung dafür, und damit produzierte Lampe

Title (fr)

Procédé pour la couverture d'un culot de lampe résistante aux éclats, appareil à cet effet, et lampe ainsi fabriquée

Publication

EP 2637196 A2 20130911 (EN)

Application

EP 13157893 A 20130305

Priority

GB 201203840 A 20120305

Abstract (en)

A method of coating an end cap of a fragment retention lamp, comprising the steps of: ## Dividing a continuous coating arranged about a first lamp (1) and a second lamp (2), whereby said division is located between one end of said first lamp and a neighbouring end of said second lamp; wherein a flap portion (11,12) formed by dividing said coating extends beyond an end cap (3) located at said first end of said first lamp (1); and ## Arranging said flap portion (11,12) over a centre portion of an end face of said end cap (3). The application further concerns an apparatus for carrying out the method, and a lamp manufactured thereby.

IPC 8 full level

H01J 61/35 (2006.01); **F21V 15/015** (2006.01); **H01J 61/70** (2006.01)

CPC (source: EP GB)

H01J 5/03 (2013.01 - GB); **H01J 5/08** (2013.01 - GB); **H01J 9/205** (2013.01 - GB); **H01J 61/35** (2013.01 - EP GB); **H01J 61/70** (2013.01 - EP)

Cited by

AT15737U1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2637196 A2 20130911; **EP 2637196 A3 20140827**; GB 201203840 D0 20120418; GB 2499998 A 20130911

DOCDB simple family (application)

EP 13157893 A 20130305; GB 201203840 A 20120305