

Title (en)

Printing machine with one or more printing units in the form of printing towers for double-sided multi-colour printing and a device for tempering components of one or more of the printing units

Title (de)

Druckmaschine mit einer oder mehreren als Drucktürme ausgebildeten Druckeinheiten für den beidseitigen mehrfarbigen Druck und einer Vorrichtung zur Temperierung von Bauteilen einer oder mehrerer der Druckeinheiten

Title (fr)

Machine d'impression dotée d'une ou plusieurs unités d'impression configurées sous forme de tours d'impression pour l'impression en couleur recto-verso et dispositif destiné à tempérer des éléments d'une ou plusieurs des unités d'impression

Publication

EP 2639065 B1 20140319 (DE)

Application

EP 13171778 A 20091217

Priority

- DE 102009001596 A 20090317
- DE 102009001597 A 20090317
- DE 102009001598 A 20090317
- EP 09795416 A 20091217

Abstract (en)

[origin: WO2010105711A2] The invention relates to a printing machine having one or more printing units (01) designed as printing towers for double-sided multicolor printing, and to a device for controlling the temperature of components of one or more of the printing units (01), wherein the printing unit (01) comprises a plurality of printing devices (04) disposed vertically one over the other, each having at least one component (07; 12) to be temperature-controlled, wherein the component (07; 12) to be temperature-controlled has a thermal interaction with fluid of a secondary circuit (14; 16) via an inlet (17), wherein the secondary circuit (14; 16) can have fluid of a primary circuit (19; 29, 35) metered via a feeding station (21) for controlling the temperature thereof, wherein components (07; 12) to be temperature-controlled of at least two different printing devices (04) have thermal interactions with two secondary circuits (14; 16) different from each other for controlling the temperatures thereof, wherein a selectively actuatable electrical heating appliance (26) is provided in the secondary circuit (14; 16) in addition to the feeding station (21), and that at least valves (24) and/or pumps (22) and/or heating appliances (26) associated with the two secondary circuits (14; 16) different from each other on a front machine side are disposed at different heights from each other, and/or can be fed with fluid from the primary circuit (19; 29, 35) by feeding stations (21) disposed at different heights.

IPC 8 full level

B41F 7/12 (2006.01); **B41F 13/00** (2006.01); **B41F 13/22** (2006.01); **B41F 31/00** (2006.01)

CPC (source: EP US)

B41F 7/12 (2013.01 - EP US); **B41F 13/0024** (2013.01 - EP US); **B41F 13/22** (2013.01 - EP US); **B41F 31/002** (2013.01 - EP US); **B41P 2213/734** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO SE SI SK SM TR

DOCDB simple family (publication)

WO 2010105711 A2 20100923; **WO 2010105711 A3 20101125**; CN 102348555 A 20120208; CN 102348555 B 20140305; EP 2408621 A2 20120125; EP 2408621 B1 20131204; EP 2639065 A1 20130918; EP 2639065 B1 20140319; US 2012037017 A1 20120216; US 8327762 B2 20121211

DOCDB simple family (application)

EP 2009067408 W 20091217; CN 200980158030 A 20091217; EP 09795416 A 20091217; EP 13171778 A 20091217; US 200913138640 A 20091217