

Title (en)

Method for positively connecting a flexible printing plate with a register element and/or for separating such a connection

Title (de)

Verfahren zum formschlüssigen Verbinden einer biegsamen Druckform mit einem Registerelement und/oder zum Trennen einer solchen Verbindung

Title (fr)

Procédé de liaison par complémentarité de forme d'un bloc d'impression souple avec un élément de repérage et/ou de séparation d'une telle liaison

Publication

EP 2644381 B1 20181128 (DE)

Application

EP 13160760 A 20130325

Priority

DE 102012205094 A 20120329

Abstract (en)

[origin: EP2644381A2] The method involves providing a suspension arm (03,13) in a printing mold. The suspension arm is edged at its respective ends relative to its supporting surface along a bending edge (02,12). A recess (56) is provided with an opening. The printing mold is connected with a register element in the opening of the recess. A portion of the supporting surface of the printing mold is bent by a bend under formation of a bending line. The opening of the recess is widened in comparison to an unbent state of the printing mold by elastic deformation of the printing mold in the region of the recess.

IPC 8 full level

B41F 27/00 (2006.01); **B41F 27/12** (2006.01)

CPC (source: EP)

B41F 27/005 (2013.01); **B41F 27/1281** (2013.01); **B41F 27/1287** (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102012205094 B3 20130404; EP 2644381 A2 20131002; EP 2644381 A3 20161026; EP 2644381 B1 20181128

DOCDB simple family (application)

DE 102012205094 A 20120329; EP 13160760 A 20130325