

Title (en)
METHOD, APPARATUS AND COMPUTER PROGRAM PRODUCT FOR CONTROLLING AN ACTUATOR WHEN ADJUSTING A TEMPERATURE

Title (de)
VERFAHREN, VORRICHTUNG UND COMPUTERPROGRAMMPRODUKT ZUR ANSTEUERUNG EINES STELLGLIEDS BEI DER EINSTELLUNG EINER TEMPERATUR

Title (fr)
PROCÉDÉ, APPAREIL ET PRODUIT DE PROGRAMME INFORMATIQUE POUR COMMANDER UN ACTIONNEUR LORS DE LA RÉGULATION D'UNE TEMPÉRATURE

Publication
EP 2665974 A1 20131127 (EN)

Application
EP 12736198 A 20120113

Priority
• FI 20115051 A 20110119
• FI 2012050030 W 20120113

Abstract (en)
[origin: WO2012098288A1] In the invention an actuator (303) of a thermal adjustment device (306) is controlled for adjusting the temperature in a target. For controlling the actuator there are three adjustment blocks: a first adjustment block (304), a second adjustment block (302) and a third adjustment block (305). The adjustment block is a functional entity, which concentrates on the adjustment of the operation of some specific area. The adjustment blocks can be implemented with different devices or combinations of devices or with programs functioning in devices or in a device. Dynamic operating limits, at least a maximum and a minimum, are in the method calculated in the first adjustment block based on scaling constants and scaling variables. The dynamic operating limits change based on the scaling variables. For example when the outside temperature drops, the maximum of the dynamic operating limits can increase. The control signal is defined in the second adjustment block, and it is defined based on the goal temperature, where it is desired for the temperature of the target to settle, and the measured temperature of the target. The dynamic operating limits and the control signal are read and an output signal is calculated in the third adjustment block for controlling the actuator by scaling the control signal with the dynamic operating limits, and the actuator, which controls the thermal adjustment device, is controlled based in the output signal. The output signal can thus vary from the minimum of the dynamic operating limit to the maximum of the dynamic operating limit.

IPC 8 full level
F24F 11/00 (2006.01); **G05B 13/00** (2006.01); **G05D 23/19** (2006.01)

CPC (source: EP FI US)
F24F 11/30 (2017.12 - EP FI); **F24F 11/46** (2017.12 - FI); **F24F 11/62** (2017.12 - EP FI); **F24F 11/70** (2017.12 - EP US); **G05D 23/1919** (2013.01 - EP); **G05D 23/193** (2013.01 - FI); **F24F 11/46** (2017.12 - EP)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2012098288 A1 20120726; EP 2665974 A1 20131127; EP 2665974 A4 20170125; FI 126110 B 20160630; FI 20115051 A0 20110119; FI 20115051 A 20120720; FI 20115051 L 20120720

DOCDB simple family (application)
FI 2012050030 W 20120113; EP 12736198 A 20120113; FI 20115051 A 20110119