

Title (en)
Sewing machine

Title (de)
Nähmaschine

Title (fr)
Machine à coudre

Publication
EP 2666898 B1 20150311 (DE)

Application
EP 13162251 A 20130404

Priority
DE 102012208907 A 20120525

Abstract (en)
[origin: EP2666898A1] The sewing machine (1) comprises a needle bar (9) for supporting a sewing needle, and a needle plate (11) in a support plate (10) for work piece. A feeder (13) is provided for transporting the work piece in a stitch area of the needle plate along a transport direction (12). A feeder drive (18) is formed, such that a movement curve of the feeder runs in a transport plateau between a transport starting point and a transport end point with a spacing deviation from an extremal distance of the feeder to the needle plate of not greater than 20 percentage parallel to the needle plate. An independent claim is included for a deflection gear assembly for transmitting a rotary movement of a drive shaft into a stroke movement of a driven component of a sewing machine.

IPC 8 full level
D05B 27/02 (2006.01)

CPC (source: EP KR)
D05B 27/00 (2013.01 - KR); **D05B 27/02** (2013.01 - EP KR)

Cited by
CN105113136A; CN105088547A

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2666898 A1 20131127; EP 2666898 B1 20150311; CN 103422262 A 20131204; CN 103422262 B 20161228;
DE 102012208907 A1 20131128; JP 2013244402 A 20131209; JP 6166944 B2 20170719; KR 101978311 B1 20190514;
KR 20130132297 A 20131204; TW 201400665 A 20140101; TW I588315 B 20170621

DOCDB simple family (application)
EP 13162251 A 20130404; CN 201310198530 A 20130524; DE 102012208907 A 20120525; JP 2013097423 A 20130507;
KR 20130057677 A 20130522; TW 102115878 A 20130503