Title (en)

SAFETY LOCK

Title (de) SICHERHEITSCHLOSS

. ...

Title (fr)

SERRURE DE SÛRETÉ

Publication

EP 2673433 A1 20131218 (EN)

Application

EP 12707916 A 20120131

Priority

• IT MI20110206 A 20110211

IB 2012050439 W 20120131

Abstract (en)

[origin: WO2012107856A1] A safety lock (1), comprises a frame and a bolt member (12) movably mounted on the frame and shiftable by rotation of the key in the lock between a first position corresponding to an open condition of the lock and a second position corresponding to a closed condition of the lock. At least one safety plate (4) is movably mounted on the frame and is translatable by rotation of the key in the lock to a position enabling movement of the bolt member (12). Hooking means operates between the bolt member (12) and the at least one safety plate (4), following a thrust illicitly produced on the bolt member (12). Also provided is means for enabling rotation of the safety plate (4) to a maximum lifting-up position of the safety plate itself. The hooking means comprises a hook-shaped portion (16a, 16b) formed in a safety pin (13) of the bolt member (12) adapted to cross a window (8) of the safety plate (4).

IPC 8 full level

E05B 21/00 (2006.01)

CPC (source: EP) E05B 21/00 (2013.01)

Citation (search report) See references of WO 2012107856A1

Cited by

IT201600071113A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2012107856 A1 20120816; EP 2673433 A1 20131218; EP 2673433 B1 20150624; IT 1403933 B1 20131108; IT MI20110206 A1 20120812; RU 2013141677 A 20150320; RU 2581577 C2 20160420

DOCDB simple family (application)

IB 2012050439 W 20120131; EP 12707916 A 20120131; IT MI20110206 A 20110211; RU 2013141677 A 20120131