

Title (en)

CIRCUIT ARRANGEMENT, METHOD FOR OPERATING THE LATTER AND STARTING APPARATUS

Title (de)

SCHALTUNGSANORDNUNG, VERFAHREN ZUM BETREIBEN DAFÜR UND STARTVORRICHTUNG

Title (fr)

CIRCUIT, PROCÉDÉ PERMETTANT DE FONCTIONNEMENT CORRESPONDANT ET DISPOSITIF DE DÉMARRAGE

Publication

EP 2676028 B1 20180516 (DE)

Application

EP 12702840 A 20120209

Priority

- DE 102011004156 A 20110215
- EP 2012052189 W 20120209

Abstract (en)

[origin: WO2012110390A1] The invention describes a circuit arrangement (1) for an electrical machine (2), in particular for a starting apparatus having a starter motor (2) for starting an internal combustion engine (15), in a motor vehicle, having a current-limiting apparatus (3) for limiting a starting current of the electrical machine (2), having a bridging apparatus (4) for bridging the current-limiting apparatus (3), wherein the bridging apparatus (4) can be directly connected to a high potential of a voltage source (10). In order to easily implement a stable circuit arrangement and a starting apparatus with a long service life, the bridging apparatus (4) comprises a contact opener and the contact opener is formed in a current path (83), with the result that the contact opener can be directly connected to a control switch (8) of the electrical machine (2).

IPC 8 full level

F02N 11/08 (2006.01)

CPC (source: EP)

F02N 11/087 (2013.01); **F02N 2200/044** (2013.01); **F02N 2200/063** (2013.01); **F02N 2250/02** (2013.01); **F02N 2300/106** (2013.01)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102011004156 A1 20120816; CN 103380290 A 20131030; CN 103380290 B 20170517; EP 2676028 A1 20131225; EP 2676028 B1 20180516; HU E038271 T2 20181029; WO 2012110390 A1 20120823

DOCDB simple family (application)

DE 102011004156 A 20110215; CN 201280008840 A 20120209; EP 12702840 A 20120209; EP 2012052189 W 20120209; HU E12702840 A 20120209