

Title (en)
TIRE

Title (de)
REIFEN

Title (fr)
PNEU

Publication
EP 2682280 A4 20150107 (EN)

Application
EP 12752892 A 20120228

Priority

- JP 2011042300 A 20110228
- JP 2011062005 A 20110322
- JP 2011062006 A 20110322
- JP 2012054966 W 20120228

Abstract (en)
[origin: US2013319593A1] Provided is a tire in which durability is improved without involving increase in the weight of the tire by the improvement of a reinforcing member. By the improvement of a reinforcing member used for a carcass ply or a reinforcing member for reinforcing a tread portion, a tire in which other performance are not compromised and the lightweight is attained is provided. Provided is a tire including a pair of left-and-right bead portions 11 and side wall portions 12 and a tread portion 13 bridging between both side wall portions 12. A reinforcing member 5 composed of a knitted fabric using a reinforcing cord is arranged in the tire circumferential direction in a ring-shape.

IPC 8 full level
B60C 5/01 (2006.01); **B60C 9/11** (2006.01); **B60C 9/18** (2006.01); **B60C 13/00** (2006.01)

CPC (source: EP US)
B60C 9/11 (2013.01 - EP US); **B60C 9/1807** (2013.01 - EP US); **Y10T 152/10765** (2015.01 - EP US)

Citation (search report)

- No further relevant documents disclosed
- See references of WO 2012118091A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
US 2013319593 A1 20131205; CN 103391854 A 20131113; CN 103391854 B 20160420; EP 2682280 A1 20140108; EP 2682280 A4 20150107;
EP 2682280 B1 20170329; JP 6051155 B2 20161227; JP WO2012118091 A1 20140707; WO 2012118091 A1 20120907

DOCDB simple family (application)
US 201213985978 A 20120228; CN 201280009773 A 20120228; EP 12752892 A 20120228; JP 2012054966 W 20120228;
JP 2013502374 A 20120228