

Title (en)

A method for methanation of gasification derived producer gas on metal catalysts in the presence of sulfur

Title (de)

Verfahren zur Methanierung des aus Gasifizierung abgeleiteten Herstellergases auf Metallkatalysatoren in Gegenwart von Schwefel

Title (fr)

Procédé destiné à produire un mélange gazeux riche en méthane à partir de gaz de synthèse contenant du soufre provenant d'une gazéification

Publication

EP 2684856 A1 20140115 (EN)

Application

EP 12175567 A 20120709

Priority

EP 12175567 A 20120709

Abstract (en)

The present invention discloses a method for catalytic production of a methane-rich gas mixture from sulfur-containing synthesis gas with simultaneous at least partial sulfur removal, thereby: a) producing a synthesis gas mixture; b) bringing said synthesis gas mixture into a contact with a methanation catalyst thereby continuously deactivating the methanation catalyst by sulfur and/or carbon species comprised in the synthesis gas mixture in one part of the methanation process, while a part of said depleted methanation catalyst is simultaneously regenerated by oxidation in a different part of the process; c) the methanation catalyst is a metal, a metal oxide, a metal sulfide or a mixture of metals, metal oxides or metal sulfide/nitride/phosphide on a support; d) said metal or metals are selected from a group comprising Ni, Ru, Mo, Co, Fe, Rh, Pd, Pt, Ir, Os, W, V, wherein the support is an oxide of a group comprising Al 2O_3 , SiO 2 , TiO 2 , CeO 2 , ZrO 2 , carbides, nitrides, phosphides or a mixture thereof, wherein e) the metal or metals can be promoted by one or more of the following elements: K, P, Na, Ba, Ni, Ru, Rh, Co, Pt, Pd, Ir, W, Os, V, Mn. The method achieves a nearly complete methanation of CO in the presence of both organic and inorganic sulfur compounds, such as olefins, tars etc., combined with an at least partial uptake of sulfur followed by a relatively fast oxidative regeneration of the methanation catalyst (bed material) and sulfur release, preferably at a temperature level near the methanation temperature.

IPC 8 full level

C07C 1/04 (2006.01); **C07C 9/04** (2006.01); **C10L 3/06** (2006.01)

CPC (source: EP)

C10L 3/08 (2013.01); **C10L 3/103** (2013.01); **C10L 3/104** (2013.01)

Citation (applicant)

- GB 2065490 A 19810701 - HALDOR TOPSOE AS
- US 4177202 A 19791204 - CHANG CLARENCE D [US], et al
- EP 2167617 A1 20100331 - SCHERRER INST PAUL [CH]
- US 2009114093 A1 20090507 - LI LIYU [US], et al
- US 4155990 A 19790522 - KIMURA SHOICHI [JP], et al
- US 4260518 A 19810407 - KATZER JAMES R, et al
- US 2455419 A 19481207 - JOHNSON EVERETT A
- US 2987486 A 19610606 - CARR NORMAN L
- US 2011039686 A1 20110217 - LI LIYU [US], et al
- L.P.L.M. RABOU; L. BOS: "High efficiency production of substitute natural gas from biomass", APPLIED CATALYSIS B: ENVIRONMENTAL, vol. 111-112, 2012, pages 456 - 460
- P.Y. HOU; H. WISE: "Kinetic Studies with a sulfur tolerant Methanation catalyst", J. CATAL., vol. 93, 1985, pages 409 - 416
- AGUINAGA; MONTES, APPLIED CATALYSIS A: GENERAL, REGENERATION OF A NICKEL / SILICA CATALYST POISONED BY THIOPHENE, 1992

Citation (search report)

- [I] US 4728672 A 19880301 - YOSHINARI TOMOHIRO [JP], et al
- [I] US 4155990 A 19790522 - KIMURA SHOICHI [JP], et al

Cited by

CN110152651A; CN107029726A; EP2977103A1; CN108855230A; CN105688919A; GB2526188A; GB2526188B; US9840446B2; WO2015159044A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2684856 A1 20140115; DK 2870125 T3 20190211; EP 2870125 A1 20150513; EP 2870125 B1 20181107; WO 2014009146 A1 20140116

DOCDB simple family (application)

EP 12175567 A 20120709; DK 13734007 T 20130625; EP 13734007 A 20130625; EP 2013063288 W 20130625