

Title (en)

ISOLATING TARGET CELLS FROM A BIOLOGICAL FLUID

Title (de)

ISOLIERUNG VON ZIELZELLEN AUS EINER BIOLOGISCHEN FLÜSSIGKEIT

Title (fr)

ISOLEMENT DE CELLULES CIBLE À PARTIR D'UN FLUIDE BIOLOGIQUE

Publication

EP 2686106 A1 20140122 (EN)

Application

EP 12711474 A 20120313

Priority

- SG 2011019775 A 20110318
- SG 2012000084 W 20120313

Abstract (en)

[origin: WO2012128717A1] A micro-fluidic device (10) operable to isolate target cells from a biological fluid and a method of isolating target cells from a biological fluid are disclosed. The micro-fluidic device (10) comprises: an inlet (50) operable to receive the biological fluid, the biological fluid comprising target cells and other components; an waste outlet (60) operable to receive at least the other components of the biological fluid; a plurality of parallel arrays of cell isolation wells (190) coupling the inlet (50) with the waste outlet (60), each parallel array of cell isolation wells (190) supporting a flow of the biological fluid from the inlet (50) to the waste outlet (60) in response to a pressure differential thereacross, each array of cell isolation wells (190) comprising a plurality isolation wells, each isolation well being dimensioned to mechanically trap the target cells therein whilst permitting flow of other components of the biological fluid; and at least one pressure maintenance structure operable to assist in maintaining a predetermined pressure differential across each of the plurality of parallel arrays of cell isolation wells (190). An increased volume of fluid can be processed using an increased number of traps in order to increase the number of target cells which are retained. By providing the arrays in parallel, the volume of sample that can be processed per unit time may be increased. This may reduce the processing time of a sample whilst increasing the efficiency of target cell isolation. Also, by using pressure maintenance structures (40), each of the parallel arrays of cell isolation structures may be operated effectively to ensure correct processing of the sample. This helps to ameliorate the problem of increasing the scale of the micro-fluidic device (10) which is difficult because it is difficult to reliably achieve a predictable flow in the presence of samples having wide-varying characteristics.

IPC 8 full level

B01L 3/00 (2006.01)

CPC (source: EP)

B01L 3/502761 (2013.01); **B01L 2200/0652** (2013.01); **B01L 2300/0816** (2013.01); **B01L 2300/0864** (2013.01); **B01L 2400/0487** (2013.01); **B01L 2400/086** (2013.01)

Citation (search report)

See references of WO 2012128717A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2012128717 A1 20120927; CN 103459034 A 20131218; EP 2686106 A1 20140122; SG 184592 A1 20121030; SG 192848 A1 20130930

DOCDB simple family (application)

SG 2012000084 W 20120313; CN 201280014262 A 20120313; EP 12711474 A 20120313; SG 2011019775 A 20110318; SG 2013062898 A 20120313