

Title (en)

Method for patinating products made of copper or a copper alloy as well as products produced by the said process

Title (de)

Verfahren zum Patinieren von Produkten aus Kupfer oder aus einer Kupferlegierung sowie Produkte hergestellt nach diesem Verfahren

Title (fr)

Procédé destiné à patiner des produits en cuivre ou en alliage de cuivre et produits fabriqués selon ce procédé

Publication

EP 2687298 B1 20160810 (DE)

Application

EP 13003071 A 20130615

Priority

DE 102012014280 A 20120719

Abstract (en)

[origin: EP2687298A1] The method comprises bringing a product in contact with a patination solution to form a patina layer, applying an aqueous polymer dispersion to the formed patina layer, and adding the patination solution and/or aqueous polymer dispersion pigments. Pigments other than the patination solution are added as polymer dispersion. A concentration of the pigments in the patination solution differs from a concentration of the pigments in the polymer dispersion. The patination solution added pigments do not form the patina layer. The method comprises bringing a product in contact with a patination solution to form a patina layer, applying an aqueous polymer dispersion to the formed patina layer, and adding the patination solution and/or aqueous polymer dispersion pigments. Pigments other than the patination solution are added as polymer dispersion. A concentration of the pigments in the patination solution differs from a concentration of the pigments in the polymer dispersion. The patination solution added pigments do not form the patina layer. The aqueous polymer dispersion penetrates a water vapor diffusion-transmissive composite into ranges near a surface of a porous patina, and is dried with the patina formation. The aqueous polymer dispersion (1-15 g/m²) is applied to the patinated surface with a solid content of 0.34-5 g/m² in a dried state. A concentration of admixture of pigments and the aqueous polymer dispersion is 5-10 wt.% based on nonionic and anionic wetting agents of an inorganic pigment dispersions used in an aqueous paint on acrylate. The method utilizes phenol, alkyl, ethoxylate and formaldehyde free pigment dispersion. The pigment dispersion comprises 50-70% of the pigments. An independent claim is included for a product made from copper or its alloy.

IPC 8 full level

B05D 5/06 (2006.01); **B05D 1/02** (2006.01); **B05D 3/02** (2006.01)

CPC (source: EP RU)

B05D 5/06 (2013.01 - RU); **B05D 5/062** (2013.01 - EP); **B05D 7/14** (2013.01 - RU); **C23C 22/63** (2013.01 - RU); **C23C 22/83** (2013.01 - EP); **B05D 1/02** (2013.01 - EP); **B05D 3/0263** (2013.01 - EP); **B05D 2202/45** (2013.01 - EP); **B05D 2502/00** (2013.01 - EP); **B05D 2601/02** (2013.01 - EP)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2687298 A1 20140122; EP 2687298 B1 20160810; DE 102012014280 A1 20140123; RU 2013133466 A 20150127; RU 2630564 C2 20170911

DOCDB simple family (application)

EP 13003071 A 20130615; DE 102012014280 A 20120719; RU 2013133466 A 20130718