

Title (en)

METHOD AND DEVICE FOR THE POWER SUPPLY FOR RACK AND PINION LIFTS

Title (de)

VERFAHREN UND VORRICHTUNG ZUR STROMVERSORGUNG FÜR ZAHNSTANGENGENAUFZÜGE

Title (fr)

PROCÉDÉ ET DISPOSITIF PERMETTANT UNE ALIMENTATION ÉLECTRIQUE POUR DES ASCENSEURS À CRÉMAILLÈRE

Publication

**EP 2691333 A1 20140205 (EN)**

Application

**EP 11862820 A 20110329**

Priority

SE 2011050359 W 20110329

Abstract (en)

[origin: WO2012134363A1] The invention concerns a method and an arrangement for the power supply for a lift of the type in which drive machinery (109) is supported by a load carrier (107) and can drive the load carrier in a first and a second direction along a track along an essentially vertical mast (110) by means of the interaction between a cogged wheel (111) and cogged rod (112). In order to reduce the requirement for external power and in this way to reduce the costs of the power supply system of the lift as a whole, the method is proposed according to: that a load carrier (107) is arranged, that the load carrier (107) is arranged to support an electrically operated electric motor (109) that is a component of the drive machinery, which electric motor is selected such that it generates a flow of energy during regenerative operation, that the electric motor (109) is arranged such that it can drive the load carrier (107) in the first direction along the track and can drive the load carrier during inverse regenerative operation to generate a flow of energy during braking and motion in the second direction along the track, that the load carrier (107) is arranged to support an energy storage system (10) that includes an energy store (60) designed to store, receive and release electrical energy, that the load carrier (107) is provided with a first current-transfer bus (11) that allows the energy flow that is emitted from the electric motor (109) during braking and regenerative operation to be transferred from the electric motor to the energy store (60) that is part of the energy storage system (10) and, when necessary, to be inversely transferred from the energy store to the drive motor, and that the load carrier (107) is arranged to increase its potential energy during acceleration or motion upwards along the mast through the influence of energy that has been obtained from the energy store (60).

IPC 8 full level

**B66B 9/02** (2006.01); **B66B 1/30** (2006.01); **B66B 9/16** (2006.01); **B66B 11/00** (2006.01); **B66B 11/04** (2006.01)

CPC (source: EP)

**B66B 1/302** (2013.01); **B66B 9/16** (2013.01); **B66B 11/005** (2013.01); **B66B 11/0461** (2013.01)

Cited by

WO2020089606A3; EP3223420B1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**WO 2012134363 A1 20121004**; CN 103492303 A 20140101; CN 103492303 B 20160518; EP 2691333 A1 20140205; EP 2691333 A4 20141119; EP 2691333 B1 20181212; ES 2724748 T3 20190913

DOCDB simple family (application)

**SE 2011050359 W 20110329**; CN 201180069700 A 20110329; EP 11862820 A 20110329; ES 11862820 T 20110329