

Title (en)

METHOD FOR CONTROLLING DEHYDRATION IN DRUM WASHING MACHINE

Title (de)

VERFAHREN ZUR STEUERUNG DER DEHYDRIERUNG IN EINER TROMMELWASCHMASCHINE

Title (fr)

PROCÉDÉ POUR COMMANDER UNE DÉSHYDRATATION DANS UNE MACHINE À LAVER À TAMBOUR

Publication

EP 2692929 A2 20140205 (EN)

Application

EP 12765059 A 20120327

Priority

- KR 20110027479 A 20110328
- KR 20110027480 A 20110328
- KR 2012002210 W 20120327

Abstract (en)

A method for controlling dehydration in a drum washing machine, which repetitively measures an unbalance value at different speeds during balance spin-drying for spreading laundry items before main spin-drying is performed in a drum washing machine, and senses an unbalance for forward and backward directions of a drum as well as an unbalance for the rotational direction of the drum so that the laundry items are redistributed in a relatively normal manner. Thus, since vibrations of the tub may be reduced during the spin-drying process, the spin-drying efficiency may be improved.

IPC 8 full level

D06F 23/02 (2006.01); **D06F 33/02** (2006.01); **D06F 49/04** (2006.01)

CPC (source: EP US)

D06F 33/40 (2020.02 - EP US); **D06F 33/48** (2020.02 - EP US); **D06F 34/20** (2020.02 - EP US); **D06F 2103/04** (2020.02 - EP US); **D06F 2103/18** (2020.02 - EP US); **D06F 2103/26** (2020.02 - EP US); **D06F 2105/02** (2020.02 - EP US); **D06F 2105/08** (2020.02 - EP US); **D06F 2105/46** (2020.02 - EP US)

Cited by

CN106232889A; US11840791B2; WO2015126166A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2692929 A2 20140205; **EP 2692929 A4 20150408**; CN 103443348 A 20131211; US 2014021140 A1 20140123; WO 2012134139 A2 20121004; WO 2012134139 A3 20130110

DOCDB simple family (application)

EP 12765059 A 20120327; CN 201280015325 A 20120327; KR 2012002210 W 20120327; US 201214008521 A 20120327