

Title (en)
MAINTENANCE VEHICLE

Title (de)
INSTANDHALTUNGSFAHRZEUG

Title (fr)
VÉHICULE D'ENTRETIEN

Publication
EP 2694346 B1 20160518 (DE)

Application
EP 12709527 A 20120310

Priority
• DE 202011004799 U 20110402
• EP 2012001085 W 20120310

Abstract (en)
[origin: WO2012136301A1] A maintenance vehicle has a vehicle frame (8) which extends in a longitudinal direction (5) of the vehicle and has, in each case at one frame end (6), a rail bogie (4) which can be moved on rails (2) of a track (3). A working space, which is open towards the track (3), is provided in a region located between the two rail bogies (4) which are spaced apart from one another. A clamping device (13) which is designed to connect the vehicle frame (8) to the rails (2) in a frictionally locking fashion, is respectively arranged at each frame end (6). At least one of the clamping devices (13) is designed to be adjustable in the longitudinal direction (5) of the vehicle relative to the vehicle frame (8) by means of a drive (17).

IPC 8 full level
B61D 15/00 (2006.01); **E01B 29/46** (2006.01)

CPC (source: EP)
B61D 15/00 (2013.01); **E01B 29/46** (2013.01)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
DE 202011004799 U1 20110609; AU 2012239075 A1 20131017; AU 2012239075 B2 20160414; CN 103534159 A 20140122; CN 103534159 B 20160316; DK 2694346 T3 20160829; EP 2694346 A1 20140212; EP 2694346 B1 20160518; ES 2587843 T3 20161027; HU E028231 T2 20161228; JP 2014514473 A 20140619; JP 6038118 B2 20161207; PL 2694346 T3 20161130; SI 2694346 T1 20161028; WO 2012136301 A1 20121011

DOCDB simple family (application)
DE 202011004799 U 20110402; AU 2012239075 A 20120310; CN 201280017135 A 20120310; DK 12709527 T 20120310; EP 12709527 A 20120310; EP 2012001085 W 20120310; ES 12709527 T 20120310; HU E12709527 A 20120310; JP 2014503009 A 20120310; PL 12709527 T 20120310; SI 201230685 A 20120310