

Title (en)
FOLLICLE UNIT EXTRACTION DEVICE

Title (de)
VORRICHTUNG ZUR EXTRAKTION VON FOLLIKELEINHEITEN

Title (fr)
DISPOSITIF D'EXTRACTION D'UNITÉ FOLLICULAIRE

Publication
EP 2699176 A2 20140226 (EN)

Application
EP 12774153 A 20120420

Priority
• US 201161477233 P 20110420
• US 201261603525 P 20120227
• US 2012034571 W 20120420

Abstract (en)
[origin: WO2012145710A2] A follicular unit extraction device comprises a handpiece for holding a follicle punch at its distal end which extends from the handpiece and terminates distally in a cutting edge. The punch is releasably coupled to a motor-driven drive shaft within the handpiece for rotation therewith. A portion of the driveshaft is tubular, and houses a piston that can move towards and away from the punch. An ejector pin is also supported within the tubular portion of the driveshaft distally of the ejector piston and is positioned to move towards the cutting edge of the punch when pushed by the piston. The handpiece and driveshaft have respective fluid inlet ports. The clearance between the piston and driveshaft interior, and the clearance between the ejector pin and punch interior, define a fluid path for conducting fluid entering the handpiece and drive shaft via inlet ports so that the fluid exits the punch at its cutting edge. The clearances limit the quantity of fluid exiting the punch to the small amount needed to protect the follicle to be extracted. Means are provided for selectively increasing the flow rate of the fluid entering the handpiece beyond the limit imposed by said clearances to thereby increase the fluid pressure within the driveshaft, moving the piston distally and, consequently, moving the pin towards the cutting edge of the punch to eject impacted graft or debris. Bias means returns the piston proximally when the flow rate is reduced below the level required to overcome the bias means.

IPC 8 full level
A61B 17/32 (2006.01); **A61B 17/3205** (2006.01); **A61F 2/10** (2006.01)

CPC (source: EP US)
A45D 26/00 (2013.01 - US); **A61B 17/32053** (2013.01 - EP US); **A61B 17/322** (2013.01 - EP US); **A61B 2017/00752** (2013.01 - EP US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2012145710 A2 20121026; **WO 2012145710 A3 20140313**; EP 2699176 A2 20140226; EP 2699176 A4 20150128;
EP 2699176 B1 20180228; ES 2665038 T3 20180424; US 2014031839 A1 20140130; US 2015305472 A1 20151029; US 9095368 B2 20150804

DOCDB simple family (application)
US 2012034571 W 20120420; EP 12774153 A 20120420; ES 12774153 T 20120420; US 201213885254 A 20120420;
US 201514750355 A 20150625