

Title (en)
FITTING FOR CORNER CABINETS

Title (de)
BESCHLAG FÜR ECKSCHRÄNKE

Title (fr)
FERRURE DE PLACARD D'ANGLE

Publication
EP 2713816 A1 20140409 (DE)

Application
EP 11726698 A 20110523

Priority
EP 2011002548 W 20110523

Abstract (en)
[origin: WO2012159641A1] The invention relates to a fitting for corner cabinets (1), in particular for kitchen corner cabinets, with an essentially rectangular interior (2) from the top view, which is accessible from the front side via a corner cabinet door (3). Said fitting consists of at least one support which can be supported in a stationary manner in the interior (2) of the corner cabinet, for maintaining at least one single-piece shelf (5) having a semi-circular base shape. Said support comprises at least one guide member (6) which supports the shelf (5) in an articulated manner and moves the shelf (5) on a predetermined movement path from an inner position in the interior (2) of the corner cabinet (1) to an outer position essentially in front of a door opening of corner cabinet (1), which is pivotably connected and in an articulated manner by means of a guide member joint axis to the lower side of the shelf (5) and by means of a support fitting, to a corner cabinet part, in particular a side wall part (4). A pull-in device (11) is associated with the shelf (5) and the guide element (6), for automatically pulling-in the shelf (5) and the guide element (6) into the interior (2) of the corner cabinet (1) from a determinable intermediate pivotable position of the shelf (5) during a closing movement. The aim of the invention is to produce a fitting which enables the shelf to be automatically pulled-in together with the guide element from a predeterminable intermediate position in a simple manner. Said pull-in device (11) is supported by itself on the guide element (6) and has a joint axis which is coaxial to the guide element joint axis on the lower side of the shelf (5), and comprises an adjusting device (15) which interacts with a drive device (10) provided on the shelf and can be moved in relation to the guide element (6).

IPC 8 full level
A47B 81/00 (2006.01); **A47B 96/02** (2006.01)

CPC (source: EP US)
A47B 81/002 (2013.01 - EP US); **A47B 96/024** (2013.01 - US); **A47B 96/025** (2013.01 - US)

Citation (search report)
See references of WO 2012159641A1

Cited by
DE202016004737U1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2012159641 A1 20121129; CN 103547189 A 20140129; CN 103547189 B 20160817; DK 2713816 T3 20160502; EP 2713816 A1 20140409; EP 2713816 B1 20160127; ES 2568473 T3 20160429; PL 2713816 T3 20160729; US 2014225492 A1 20140814; US 9119470 B2 20150901

DOCDB simple family (application)
EP 2011002548 W 20110523; CN 201180071088 A 20110523; DK 11726698 T 20110523; EP 11726698 A 20110523; ES 11726698 T 20110523; PL 11726698 T 20110523; US 201114119531 A 20110523