

Title (en)
CONTROLLABLE LIFT BRAKE

Title (de)
REGELBARE AUFZUGSBREMSE

Title (fr)
FREIN D'ASCENSEUR RÉGLABLE

Publication
EP 2714565 B1 20150114 (DE)

Application
EP 12723687 A 20120525

Priority

- EP 11168118 A 20110530
- EP 2012059796 W 20120525
- EP 12723687 A 20120525

Abstract (en)
[origin: WO2012163812A1] The invention relates to a method for controlling an elevator brake having a housing (4) and a brake unit (3), which is movable in the axial direction on a path between a braking position and a starting position and comprises at least one pulling unit (6), which brake unit (3) is moved at least by means of a first spring force (FBF) of at least one brake spring (BF). According to the invention, a lifting unit (5), which produces a lift (H, H1, H2), on the pulling unit (6) of the brake unit (3) produces a movement in the axial direction counter to the spring force (FBF) of the at least one brake spring (BF). By means of a second spring force (FAF) of an equalisation spring (AF) tensioned by the lift (H, H1, H2) of the lifting unit (5), the first spring force (FBF) of the at least one brake spring (BF) is reduced.

IPC 8 full level
B66B 5/18 (2006.01)

CPC (source: EP US)
B66B 5/18 (2013.01 - EP US); **B66D 5/14** (2013.01 - EP US); **B66D 5/30** (2013.01 - EP US)

Cited by
US11975945B1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2012163812 A1 20121206; AU 2012264897 A1 20130822; BR 112013024797 A2 20161220; CA 2826847 A1 20121206;
CN 103562109 A 20140205; EP 2714565 A1 20140409; EP 2714565 B1 20150114; SG 194430 A1 20131230; US 2012305338 A1 20121206

DOCDB simple family (application)
EP 2012059796 W 20120525; AU 2012264897 A 20120525; BR 112013024797 A 20120525; CA 2826847 A 20120525;
CN 201280026492 A 20120525; EP 12723687 A 20120525; SG 2013063433 A 20120525; US 201213483400 A 20120530