

Title (en)

APPARATUS FOR ON DEMAND DUST AND/OR MOISTURE PROTECTION FOR CURRENT-CARRYING APPLIANCE CONNECTION OR CONNECTING MEANS

Title (de)

VORRICHTUNG ZUM BEDARFSWEISEN STAUB- UND/ODER FEUCHTIGKEITSSCHUTZ FÜR STROMFÜHRENDE GERÄTEANSCHLUSS- ODER VERBINDUNGSMITTEL

Title (fr)

DISPOSITIF PERMETTANT DE RÉALISER, EN CAS DE BESOIN, UNE PROTECTION CONTRE LA POUSSIÈRE ET/OU L'HUMIDITÉ POUR DES MOYENS CONDUCTEURS D'ÉLECTRICITÉ SERVANT À RACCORDER OU CONNECTER DES APPAREILS

Publication

EP 2727189 A1 20140507 (DE)

Application

EP 12729973 A 20120626

Priority

- DE 102011106159 A 20110630
- DE 102011109858 A 20110809
- EP 2012062276 W 20120626

Abstract (en)

[origin: WO2013000875A1] The invention relates to an apparatus for temporary dust and/or moisture protection for current-carrying connecting means, containing a standard appliance plug which can be connected to a standard appliance plug socket which is a constituent part of an electrical connection cable or other connecting means. According to the invention, the standard appliance plug is surrounded by a housing which is open in the insertion direction and which has an attachment flange for accommodating a circumferential sealing means. The housing has means for attachment to or in a device which is intended to be supplied with electrical energy. Furthermore, the extent of the housing wall in the insertion direction and the clearance between the wall inner face and the standard appliance plug is such that the standard plug socket can be introduced without obstruction. The standard plug socket is integrated or accommodated in a sealing housing which is open in the insertion direction, wherein the inner contour of the sealing housing is designed to complement the contour of the housing wall of the standard plug housing in such a way that, during the insertion process, both the electrical connection is established and the sealing housing of the plug socket forms a close interlocking connection and comes into contact with the standard plug housing, wherein the housing wall is surrounded on the outside.

IPC 8 full level

H01R 13/52 (2006.01); **H01R 13/625** (2006.01); **H01R 13/639** (2006.01); **H01R 13/74** (2006.01); **H01R 27/00** (2006.01)

CPC (source: EP)

H01R 13/5213 (2013.01); **H01R 13/5219** (2013.01); **H01R 13/639** (2013.01); **H01R 13/625** (2013.01); **H01R 13/74** (2013.01);
H01R 27/00 (2013.01)

Citation (search report)

See references of WO 2013000875A1

Cited by

CN111952770A

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102011109858 A1 20130103; EP 2727189 A1 20140507; EP 2727189 B1 20171220; WO 2013000875 A1 20130103

DOCDB simple family (application)

DE 102011109858 A 20110809; EP 12729973 A 20120626; EP 2012062276 W 20120626