

Title (en)  
DEVICE FOR CLOSING CONTAINERS

Title (de)  
VORRICHTUNG ZUM VERSCHLIESSEN VON BEHÄLTERN

Title (fr)  
DISPOSITIF POUR LA FERMETURE DE RÉCIPIENTS

Publication  
**EP 2736834 B1 20180221 (DE)**

Application  
**EP 12727301 A 20120602**

Priority  
• DE 102011108428 A 20110726  
• EP 2012002350 W 20120602

Abstract (en)  
[origin: WO2013013735A1] The invention relates to a device for closing containers (2) comprising a plurality of closer stations (1) formed at the periphery of a rotor (16) which can be driven to circulate around the vertical machine axis (X), which closer stations each have a closer tool (3). The device is characterized in that the respective closer station (1) has a magnetically acting coupling element (9) which has a first, inner magnet element (10) and a second, outer magnet element (11), wherein a drive space (26) separate from a product space (27) is formed, and which second, outer magnet element (11) is positively guided on a linear guide (13) and takes along the closer tool (3) via a driver (14) in a required height movement, likewise with positive guidance. In an exemplary embodiment, a separating wall (12) is arranged between the first, inner magnet element (10) and the second, outer magnet element (11).

IPC 8 full level  
**B67B 3/20** (2006.01)

CPC (source: EP US)  
**B67B 3/2033** (2013.01 - EP US); **B67B 3/2053** (2013.01 - EP US); **B67B 3/2066** (2013.01 - US); **B67B 3/268** (2013.01 - EP US); **B67B 2201/08** (2013.01 - EP US)

Cited by  
US11713147B2

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**DE 102011108428 A1 20130131**; BR 112013032507 A2 20170301; EP 2736834 A1 20140604; EP 2736834 B1 20180221; SI 2736834 T1 20180430; US 2014174029 A1 20140626; US 9567198 B2 20170214; WO 2013013735 A1 20130131

DOCDB simple family (application)  
**DE 102011108428 A 20110726**; BR 112013032507 A 20120602; EP 12727301 A 20120602; EP 2012002350 W 20120602; SI 201231252 T 20120602; US 201214234689 A 20120602