

Title (en)
METHOD FOR PRODUCING A PRINTING STENCIL FOR TECHNICAL PRINTING, AND PRINTING STENCIL FOR TECHNICAL PRINTING

Title (de)
VERFAHREN ZUM HERSTELLEN EINER DRUCKSCHABLONE FÜR DEN TECHNISCHEN DRUCK UND DRUCKSCHABLONE FÜR DEN TECHNISCHEN DRUCK

Title (fr)
PROCÉDÉ DE PRODUCTION D'UN POCHOIR POUR L'IMPRESSION TECHNIQUE, ET POCHOIR POUR L'IMPRESSION TECHNIQUE CORRESPONDANT

Publication
EP 2750891 B1 20190320 (DE)

Application
EP 12758819 A 20120830

Priority
• DE 102011081837 A 20110830
• EP 2012066855 W 20120830

Abstract (en)
[origin: WO2013030273A1] The present invention relates to a method for producing a printing stencil for technical printing, for applying a printed pattern to a substrate, and to a printing stencil. The method comprises supplying a carrier layer (21) for the printing stencil, supplying a structure layer (22) for the printing stencil, this layer being located beneath the carrier layer (21), making an elongate printed-image opening (22a), corresponding to at least part of the printed pattern, in the structure layer (22), and making carrier-layer openings (21a) in the carrier layer (21) in the region of the printed-image opening (22a). The method is characterized in that, for making the carrier-layer openings (21a), use is made of a laser device which is designed to emit a laser beam in laser pulses, and the task of making the carrier-layer openings (21) comprises making a row of carrier-layer openings (21a) extending in the longitudinal direction of the printed-image opening, wherein, for making each carrier-layer opening (21) in the row, a focussing means of the laser device is positioned at a position of the respective carrier-layer opening (21), and the respective carrier-layer opening (21) is made by means of one or more laser pulses at this position (P1), and the focussing means of the laser device, once a carrier-layer opening has been made, between two successive laser pulses, is displaced relative to the carrier layer, and in the longitudinal direction of the elongate printed-image opening (22a), from the position (P1) of the carrier-layer opening (21a) which has been made to the position (P2) of the carrier-layer opening which is subsequently to be made.

IPC 8 full level
B41C 1/14 (2006.01); **B41N 1/24** (2006.01); **H05K 3/12** (2006.01)

CPC (source: EP US)
B41C 1/145 (2013.01 - EP US); **B41N 1/24** (2013.01 - EP US); **B41N 1/248** (2013.01 - US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
DE 102011081837 A1 20130228; **DE 102011081837 B4 20210805**; CN 104023981 A 20140903; CN 104023981 B 20160817; EP 2750891 A1 20140709; EP 2750891 B1 20190320; JP 2014531338 A 20141127; JP 6231478 B2 20171115; MY 185079 A 20210430; US 2014305323 A1 20141016; US 9296195 B2 20160329; WO 2013030273 A1 20130307

DOCDB simple family (application)
DE 102011081837 A 20110830; CN 201280050248 A 20120830; EP 12758819 A 20120830; EP 2012066855 W 20120830; JP 2014527656 A 20120830; MY PI2014000557 A 20120830; US 201214342076 A 20120830