

Title (en)  
Heelbinding with a ski brake for a mountaineering ski binding

Title (de)  
Hinterbacken mit einer Skibremse für eine Skitourenbindung

Title (fr)  
Mâchoire arrière dotée d'un frein de ski pour une fixation de ski de randonnée

Publication  
**EP 2774660 A3 20141119 (DE)**

Application  
**EP 14158302 A 20140307**

Priority  
DE 102013204065 A 20130308

Abstract (en)  
[origin: EP2774660A2] The device (100) has a stopper lever (140) having a stopper portion (142), and a coupling region (141). The stopper lever is pivotally coupled about a rotation axis (102) relative to a base body (106). The stopper lever is pivotally mounted with the coupling region about another rotation axis (103). The stopper lever is coupled to an adjusting lever (120) such that a rotation of the adjusting lever causes rotation of the stopper lever about the former rotation axis. The former rotation axis is translationally displaceable along an adjusting direction (107). An independent claim is also included for a ski binding.

IPC 8 full level  
**A63C 7/10** (2006.01); **A63C 9/08** (2012.01); **A63C 9/084** (2012.01)

CPC (source: EP)  
**A63C 7/1026** (2013.01); **A63C 7/104** (2013.01); **A63C 9/0807** (2013.01); **A63C 9/0842** (2013.01)

Citation (search report)

- [A] EP 0045698 A1 19820210 - LOOK SA [FR]
- [EL] EP 2740519 A2 20140611 - ROSSIGNOL SA [FR]
- [A] WO 2012024809 A1 20120301 - FRITSCHI AG SWISS BINDINGS [CH], et al
- [A] WO 2009105866 A1 20090903 - G3 GENUINE GUIDE GEAR INC [CA], et al

Cited by  
EP3974039A1; FR3123225A1; EP3135350A1; FR3040308A1; US9868047B2

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**EP 2774660 A2 20140910; EP 2774660 A3 20141119; EP 2774660 B1 20160302**; DE 102013204065 A1 20140911;  
DE 102013204065 B4 20141106

DOCDB simple family (application)  
**EP 14158302 A 20140307**; DE 102013204065 A 20130308