

Title (en)

METHOD FOR SETTING THE SPACINGS BETWEEN CYLINDERS OF AN INKING UNIT, AND PRINTING PRESS

Title (de)

VERFAHREN ZUM EINSTELLEN DER ABSTÄNDE ZWISCHEN ZYLINDERN EINES FARBWERKES UND DRUCKMASCHINE

Title (fr)

PROCÉDÉ DE RÉGLAGE DES DISTANCES ENTRE DES CYLINDRES D'UN MÉCANISME D'ENCRAGE, ET PRESSE D'IMPRESSSION

Publication

EP 2776247 B1 20171025 (DE)

Application

EP 12779046 A 20121025

Priority

- DE 102011086047 A 20111109
- EP 2012071161 W 20121025

Abstract (en)

[origin: WO2013068239A2] Method for setting the spacings between cylinders of an inking unit which delimit at least two cylinder nips, and in which method the spacings are set on the basis of measured values which are obtained from the surface of at least one of the cylinders of the inking unit. It is considered to be novel and inventive that, during the setting of the spacing between the two cylinders which delimit a second cylinder nip, knowledge is used which was obtained during the setting of the spacing between the two cylinders which delimit a first cylinder nip. A printing press for carrying out the described method is also described and claimed.

IPC 8 full level

B41F 1/32 (2006.01); **B41F 5/24** (2006.01); **B41F 13/24** (2006.01); **B41F 31/30** (2006.01); **B41F 33/00** (2006.01); **B41F 33/10** (2006.01)

CPC (source: EP US)

B41F 5/24 (2013.01 - EP US); **B41F 13/24** (2013.01 - EP US); **B41F 31/004** (2013.01 - US); **B41F 31/30** (2013.01 - EP US); **B41F 31/32** (2013.01 - EP US); **B41F 33/0063** (2013.01 - EP US); **B41F 33/10** (2013.01 - EP US); **B41P 2200/12** (2013.01 - EP US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

DE 102011086047 A1 20130516; EP 2776247 A2 20140917; EP 2776247 B1 20171025; ES 2652035 T3 20180131; US 2014251169 A1 20140911; WO 2013068239 A2 20130516; WO 2013068239 A3 20130815

DOCDB simple family (application)

DE 102011086047 A 20111109; EP 12779046 A 20121025; EP 2012071161 W 20121025; ES 12779046 T 20121025; US 201214350641 A 20121025