

Title (en)
COMPRESSOR

Title (de)
VERDICHTER

Title (fr)
COMPRESSEUR

Publication
EP 2778421 A1 20140917 (EN)

Application
EP 12846914 A 20121107

Priority
• JP 2011244227 A 20111108
• JP 2012007141 W 20121107

Abstract (en)
The present invention provides an efficient compressor in which a suction hole 12 includes a reduced-diameter portion 12a located on the downstream side, and an increased-diameter portion 12b located on the upstream side, a non-contact length from a downstream side tip end of a suction liner 13 to the reduced-diameter portion 12a is shorter than a length of the reduced-diameter portion 12a, a heat-insulating space 16 is formed between the suction liner 13 and the increased-diameter portion 12b, an inner diameter \varnothing C1 of the reduced-diameter portion 12a is equal to an inner diameter \varnothing L of the suction liner 13, movement of heat toward suction refrigerant gas in a suction pipe path extending from the suction liner to the suction chamber is suppressed, and a pressure loss can be minimized.

IPC 8 full level
F04C 29/04 (2006.01); **F04C 18/356** (2006.01); **F04C 23/00** (2006.01); **F04C 29/12** (2006.01)

CPC (source: EP)
F04C 23/008 (2013.01); **F04C 29/04** (2013.01); **F04C 29/12** (2013.01); **F04C 18/356** (2013.01); **F04C 2240/806** (2013.01)

Cited by
EP3550147A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
EP 2778421 A1 20140917; **EP 2778421 A4 20141203**; **EP 2778421 B1 20160608**; CN 103782039 A 20140507; CN 103782039 B 20160706; JP 6112489 B2 20170412; JP WO2013069275 A1 20150402; WO 2013069275 A1 20130516

DOCDB simple family (application)
EP 12846914 A 20121107; CN 201280043347 A 20121107; JP 2012007141 W 20121107; JP 2013542847 A 20121107