

Title (en)

DOPED ORGANIC ELECTROLUMINESCENT DEVICE AND METHOD FOR PREPARING SAME

Title (de)

DOTIERTE ORGANISCHE ELEKTROLUMINESZENZE VORRICHTUNG UND VERFAHREN ZU IHRER HERSTELLUNG

Title (fr)

DISPOSITIF ÉLECTROLUMINESCENT ORGANIQUE ET PROCÉDÉ DE PRÉPARATION DE CE DISPOSITIF

Publication

**EP 2787553 A4 20151111 (EN)**

Application

**EP 11876540 A 20111128**

Priority

CN 2011083048 W 20111128

Abstract (en)

[origin: EP2787553A1] Disclosed is a doped organic electroluminescent device, comprising the following structures laminated in succession: a conductive anode substrate, a hole injecting layer, a hole transportation layer, an electron barrier layer, a light-emitting layer, an electron transportation layer, an electron injecting layer and a cathode; and the material for the electron barrier layer is a hole transportation material doped with a cerium salt. The material for an electron barrier layer in such a doped organic electroluminescent device is a hole transportation material doped with a cerium salt which has a low work function of approximately -2.0 eV and can effectively block electrons. By doping the cerium salt having a low work function into the hole transportation material as the electron barrier layer, the LUMO energy level of the hole transportation material is greatly increased, thereby elevating the potential barrier between the electron barrier layer and the light-emitting layer, so that it is difficult for the electrons to transit to the side of the hole transportation layer and a good electron barrier effect is achieved. The present invention also provides a method for preparing the doped organic electroluminescent device.

IPC 8 full level

**H01L 51/54** (2006.01); **H01L 51/50** (2006.01); **H05B 33/14** (2006.01)

CPC (source: CN EP US)

**H10K 50/11** (2023.02 - US); **H10K 50/15** (2023.02 - US); **H10K 50/155** (2023.02 - EP US); **H10K 50/16** (2023.02 - US); **H10K 50/17** (2023.02 - US); **H10K 50/171** (2023.02 - US); **H10K 50/18** (2023.02 - US); **H10K 50/181** (2023.02 - CN EP); **H10K 71/00** (2023.02 - US); **H10K 71/30** (2023.02 - CN EP US); **H10K 85/324** (2023.02 - CN EP US); **H10K 85/342** (2023.02 - CN EP US); **H10K 85/631** (2023.02 - CN EP US); **H10K 85/633** (2023.02 - US); **H10K 85/636** (2023.02 - US); **H10K 85/6565** (2023.02 - US); **H10K 85/6572** (2023.02 - CN EP US)

Citation (search report)

- [XY] US 2008136321 A1 20080612 - DO LEE MI [KR], et al
- [YA] US 2009243475 A1 20091001 - SHODA RYO [JP], et al
- [Y] YOU HAN ET AL: "Improved performances of organic light-emitting diodes with metal oxide as anode buffer", JOURNAL OF APPLIED PHYSICS, AMERICAN INSTITUTE OF PHYSICS, US, vol. 101, no. 2, 22 January 2007 (2007-01-22), pages 26105 - 026105, XP012097523, ISSN: 0021-8979
- [Y] LI L ET AL: "Surface modification and characterization of indium-tin oxide for organic light-emitting devices", JOURNAL OF MATERIALS SCIENCE: MATERIALS IN ELECTRONICS, KLUWER ACADEMIC PUBLISHERS, BO, vol. 19, no. 12, 5 January 2008 (2008-01-05), pages 1214 - 1221, XP019644513, ISSN: 1573-482X, DOI: 10.1007/S10854-007-9545-5
- See also references of WO 2013078593A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

**EP 2787553 A1 20141008**; **EP 2787553 A4 20151111**; CN 104025332 A 20140903; JP 2015503229 A 20150129; US 2015028311 A1 20150129; WO 2013078593 A1 20130606

DOCDB simple family (application)

**EP 11876540 A 20111128**; CN 2011083048 W 20111128; CN 201180074540 A 20111128; JP 2014542673 A 20111128; US 201114360922 A 20111128