

Title (en)  
SHORT-CIRCUIT FAULT INDICATOR DEVICE

Title (de)  
KURZSCHLUSS-FEHLERANZEIGEVORRICHTUNG

Title (fr)  
DISPOSITIF INDICATEUR DE DÉFAILLANCE DE TYPE COURT-CIRCUIT

Publication  
**EP 2805343 B1 20170628 (EN)**

Application  
**EP 13722850 A 20130111**

Priority  

- IN 214MU2012 A 20120120
- IN 2013000022 W 20130111

Abstract (en)  
[origin: WO2013114395A2] A short-circuit fault indicator mechanism adapted for indicating a normal operating condition, a short-circuit condition and an OFF condition of a circuit breaker is disclosed. The short-circuit indicator mechanism comprises a slider, a solenoid, and a rotating arm. The slider is having a first end connecting to a first hook. The slider is having a second end connecting to a solenoid. The slider is slidably movable between a first position and a second position responsive to a plurality of operating conditions of the circuit breaker. The rotating arm is having a second hook that engages and/or disengages with the first hook in the first and second position of the slider respectively. The rotating arm is having an indication flag that indicates the plurality of operating conditions of the circuit breaker.

IPC 8 full level  
**H01H 71/04** (2006.01)

CPC (source: EP)  
**H01H 71/04** (2013.01); **H01H 2071/042** (2013.01)

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**WO 2013114395 A2 20130808; WO 2013114395 A3 20131010**; EP 2805343 A2 20141126; EP 2805343 B1 20170628

DOCDB simple family (application)  
**IN 2013000022 W 20130111**; EP 13722850 A 20130111