

Title (en)
PRETENSIONER MECHANISM

Title (de)
VORSPANNMECHANISMUS

Title (fr)
MÉCANISME DE PRÉTENDEUR

Publication
EP 2813401 B1 20170906 (EN)

Application
EP 13747097 A 20130206

Priority
• JP 2012027504 A 20120210
• JP 2013052757 W 20130206

Abstract (en)
[origin: US2014145021A1] In a pretensioner mechanism, movement of a piston is anchored by an anchoring pin. The anchoring pin is crushed and the piston is allowed to move. Hence, a pinion is turned by a rack of the piston. A facilitating cavity is formed in the anchoring pin. Crushing and deformation of the anchoring pin in a diametric direction thereof due to a movement of the rack is facilitated by the facilitating cavity. Therefore, the anchoring pin may be easily crushed and deformed in the diametric direction by the movement of the rack, and the action of the anchoring pin caused by the movement of the rack may be effectively made consistent.

IPC 8 full level
B60R 22/46 (2006.01)

CPC (source: EP KR US)
B60R 22/46 (2013.01 - KR); **B60R 22/4604** (2013.01 - KR); **B60R 22/4633** (2013.01 - EP KR US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
US 2014145021 A1 20140529; US 9358952 B2 20160607; CN 103608218 A 20140226; CN 103608218 B 20170405; EP 2813401 A1 20141217; EP 2813401 A4 20151021; EP 2813401 B1 20170906; JP 2013163443 A 20130822; JP 5734889 B2 20150617; KR 101711509 B1 20170302; KR 20140124745 A 20141027; WO 2013118780 A1 20130815

DOCDB simple family (application)
US 20131423233 A 20130206; CN 201380001671 A 20130206; EP 13747097 A 20130206; JP 2012027504 A 20120210; JP 2013052757 W 20130206; KR 20147002323 A 20130206