

Title (en)

Rubber composition for tire, and pneumatic tire

Title (de)

Kautschukzusammensetzung für Reifen und Luftreifen damit

Title (fr)

Composition de caoutchouc pour pneu et pneu

Publication

EP 2823972 A1 20150114 (EN)

Application

EP 14164492 A 20140411

Priority

JP 2013145646 A 20130711

Abstract (en)

The present invention provide a rubber composition for a tire, capable of achieving a balanced improvement in breaking performance and fuel efficiency while simultaneously having excellent conductivity, and a pneumatic tire formed from the rubber composition. The present invention relates to a rubber composition for a tire, including a wet masterbatch that is obtained by mixing a rubber latex and a liquid dispersion of a conductive carbon black having a nitrogen adsorption specific surface area of not less than 900 m²/g and a DBP oil absorption of not less than 300 ml/100 g.

IPC 8 full level

B60C 1/00 (2006.01)

CPC (source: EP)

B60C 1/00 (2013.01); **B60C 1/0025** (2013.01); **B60C 1/0041** (2013.01); **C08J 3/22** (2013.01); **C08J 2300/26** (2013.01); **C08J 2325/10** (2013.01)

Citation (applicant)

- JP H08230407 A 19960910 - SUMITOMO RUBBER IND
- JP 2008075066 A 20080403 - SUMITOMO RUBBER IND
- JP 2009007437 A 20090115 - SUMITOMO RUBBER IND

Citation (search report)

- [A] EP 2165853 A1 20100324 - GOODYEAR TIRE & RUBBER [US]
- [AP] EP 2615131 A1 20130717 - SUMITOMO RUBBER IND [JP]
- [A] US 2009126844 A1 20090521 - NAKAMURA NORIHIKO [JP]

Cited by

CN112739760A; EP3795624A1; CN114466886A; US11732114B2; WO2019102337A1; WO2020058259A1; WO2021052736A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2823972 A1 20150114; EP 2823972 B1 20161116; JP 2015034280 A 20150219; JP 6084947 B2 20170222

DOCDB simple family (application)

EP 14164492 A 20140411; JP 2014077087 A 20140403