

Title (en)

LIGHTING APPARATUS, AND LIGHTING ADJUSTMENT METHOD

Title (de)

BELEUCHTUNGSVORRICHTUNG UND BELEUCHTUNGSEINSTELLVERFAHREN

Title (fr)

APPAREIL D'ÉCLAIRAGE, ET PROCÉDÉ D'AJUSTEMENT D'ÉCLAIRAGE

Publication

EP 2827684 B1 20180822 (EN)

Application

EP 13761464 A 20130220

Priority

- JP 2012054796 A 20120312
- JP 2013000939 W 20130220

Abstract (en)

[origin: EP2827684A1] Provided is a lighting apparatus having a constant voltage circuit, wherein the remaining capacity of a battery pack can be signaled. An input voltage detection unit (22) and a control unit (23) measure the input voltage from a battery pack (12), and when the measured voltage drops to equal to or below a dimming onset voltage (V1 the control unit (23), a light adjustment control unit (31) and an output voltage switching unit (33) adjust the output voltage to a light source unit (25) so that the dimming of the light source unit (25) is initiated.

IPC 8 full level

F21L 4/00 (2006.01); **F21V 23/00** (2015.01); **H05B 37/02** (2006.01)

CPC (source: EP US)

H05B 45/395 (2020.01 - EP US); **Y02B 20/30** (2013.01 - EP)

Citation (examination)

US 2011252678 A1 20111020 - JONES DALE [US], et al

Cited by

EP4090883A4; US11035556B2; US10412805B1; USD904657S; US11672068B2; US11589434B2; US11871487B2; US11448372B2; US11879603B2

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2827684 A1 20150121; **EP 2827684 A4 20150701**; **EP 2827684 B1 20180822**; JP 2013191304 A 20130926; WO 2013136671 A1 20130919

DOCDB simple family (application)

EP 13761464 A 20130220; JP 2012054796 A 20120312; JP 2013000939 W 20130220