

Title (en)

DEVICE FOR DETECTING THE P, R, N, D, M+, M AND M- POSITIONS OF A GEAR LEVER OF A GEARBOX OF A MOTOR VEHICLE

Title (de)

VORRICHTUNG ZUR ERFASSUNG DER POSITIONEN P, R, N, D, M +, M UND M- EINES GANGSCHALTHEBELS EINES KRAFTFAHRZEUGS

Title (fr)

DISPOSITIF DE DETECTION DES POSITIONS P, R, N, D, M+, M ET M- D'UN LEVIER DE COMMANDE D'UNE BOITE DE VITESSES D'UN VEHICULE AUTOMOBILE.

Publication

**EP 2828555 A1 20150128 (FR)**

Application

**EP 13715355 A 20130320**

Priority

- FR 1252530 A 20120321
- FR 2013050597 W 20130320

Abstract (en)

[origin: WO2013140093A1] This device is mounted with the capacity for angular motion within a supportive housing (2), said motion being detected by means capable of sending electrical signals into a processing unit. The means comprise a single 2D Hall effect sensor (4) capable of measuring only the rotations of the magnetic field, said sensor (4) being mounted to face a double magnet (5) in order to measure two rotations of the lever within two planes each corresponding to said positions P, R, N, D and M+, M and M-.

IPC 8 full level

**F16H 59/04** (2006.01); **F16H 59/10** (2006.01)

CPC (source: EP US)

**F16H 59/0204** (2013.01 - EP US); **F16H 59/044** (2013.01 - EP US); **F16H 59/105** (2013.01 - EP US); **G01B 7/003** (2013.01 - US); **B60Y 2400/3012** (2013.01 - EP US)

Citation (search report)

See references of WO 2013140093A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**WO 2013140093 A1 20130926**; EP 2828555 A1 20150128; FR 2988339 A1 20130927; FR 2988339 B1 20140404; US 2015048816 A1 20150219; US 9568092 B2 20170214

DOCDB simple family (application)

**FR 2013050597 W 20130320**; EP 13715355 A 20130320; FR 1252530 A 20120321; US 201314386738 A 20130320