

Title (en)

SAFETY SWITCH DEVICE WITH SWITCHING ELEMENT IN AN ELECTRIC PATH COMPRISING AUXILIARY CONTACTS

Title (de)

SICHERHEITSSCHALTVORRICHTUNG MIT SCHALTELEMENT IM HILFSKONTAKTSTROMPFAD

Title (fr)

DISPOSITIF DE COMMUTATION DE SÉCURITÉ COMPRENANT ÉLÉMENT DE COMMUTATION COMBINÉ INTÉGRÉ DANS UNE VOIE DE COURANT COMPRENANT CONTACTS AUXILIAIRES

Publication

EP 2834826 A1 20150211 (DE)

Application

EP 13715636 A 20130327

Priority

- DE 102012103015 A 20120405
- EP 2013056517 W 20130327

Abstract (en)

[origin: WO2013149905A1] The invention relates to a safety switching apparatus (1) for switching a technical installation (10) on or off in a failsafe manner, having a failsafe control/evaluation unit (28) with an input (34) for receiving an input signal. The failsafe control/evaluation unit (28) is designed to process the input signal in order to generate, on the basis thereof, an output signal (A) for switching the technical installation (10) on or off at an output signal time (t1, t2). The failsafe control/evaluation unit (28) has a first output (36) for transmitting the output signal (A) to an electromechanical switch (40). The electromechanical switch (40) has a normally open contact (42) for switching a load circuit (49) of the technical installation (10) and a positively driven auxiliary contact (44) in an auxiliary contact current path (45), via which a current can be carried, when a defined voltage (V1) is applied, in order to check the switching position of the normally open contact (42). A switching element (50) is arranged in the auxiliary contact current path (45). The failsafe control/evaluation unit (28) is designed to generate a switching signal (S) at a switching signal time (t3, t4) with an interval of time (Deltat3, Deltat4) from the output signal time (t1, t2), wherein the failsafe control/evaluation unit (28) has a second output (52) for transmitting the switching signal (S) to the switching element (50) which is designed to switch the current through the auxiliary contact current path (45) when the switching signal (S) is received.

IPC 8 full level

H01H 47/00 (2006.01)

CPC (source: CN EP US)

H01H 9/0271 (2013.01 - US); **H01H 9/54** (2013.01 - US); **H01H 47/004** (2013.01 - CN EP US); **H01H 2300/026** (2013.01 - CN EP US)

Citation (search report)

See references of WO 2013149905A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

DE 102012103015 A1 20131010; DE 102012103015 B4 20131205; CN 104272420 A 20150107; CN 104272420 B 20170412; EP 2834826 A1 20150211; EP 2834826 B1 20160511; HK 1204141 A1 20151106; JP 2015519632 A 20150709; JP 6316278 B2 20180425; US 2015015089 A1 20150115; US 9852852 B2 20171226; WO 2013149905 A1 20131010

DOCDB simple family (application)

DE 102012103015 A 20120405; CN 201380024217 A 20130327; EP 13715636 A 20130327; EP 2013056517 W 20130327; HK 15104625 A 20150515; JP 2015503824 A 20130327; US 201414504851 A 20141002