

Title (en)
SUCTION CONVEYOR DEVICE FOR TRANSPORTING FLAT ITEMS, AND SYSTEM FOR PRODUCING FLAT ITEMS COMPRISING SAID SUCTION CONVEYOR

Title (de)
SAUGFÖRDERVORRICHTUNG ZUM TRANSPORT VON FLACHTEILEN, UND ANLAGE ZUM HERSTELLEN VON FLACHTEILEN UMFASSEND EINER SOLCHEN SAUGFÖRDERVORRICHTUNG

Title (fr)
SYSTÈME D'ACHEMINEMENT PAR ASPIRATION POUR LE TRANSPORT D'ÉLÉMENTS PLATS ET INSTALLATION POUR LA FABRICATION D'ÉLÉMENTS PLATS COMPRENANT LEDIT SYSTÈME

Publication
EP 2841365 A1 20150304 (DE)

Application
EP 13718585 A 20130425

Priority
• DE 102012206847 A 20120425
• EP 2013058626 W 20130425

Abstract (en)
[origin: WO2013160399A1] The invention relates to a suction conveyor device (30) for transporting flat items (55), in particular sheets of paper, preferably on the path between a cutting station (20, 24) and a stack forming station (32) in the paper processing industry, said conveyor comprising a suction arrangement which has a suction side (52a) on which a low pressure is generated, and a continuously rotating flexible conveying means arrangement which is made of a flexible flat material provided with holes, and an inner side which enables the conveying means arrangement to move along the suction side (52a) of the suction arrangement, and an outer side for receiving the flat items in the active area of the suction side (52a) of the suction arrangement, where the conveying means arrangement moves in the transporting direction (A), the suction arrangement and the conveyor means arrangement being designed such that a transport path having a width (X) is defined in the active range of the suction side (52a) of the suction arrangement perpendicular to transporting direction (A). The invention is characterized in that the conveying means arrangement is formed by continuously circulating individual, single-piece, flexible conveying means (40), both lateral edges thereof (40a) extending in the transporting direction (A) being arranged at a distance from each other, said distance being at least the same size as the total width (X) of the transport path such that the individual, single-piece flexible conveyor means (40) extend at least over the total width of the transport path.

IPC 8 full level
B65H 29/24 (2006.01); **B65H 27/00** (2006.01); **B65H 35/00** (2006.01)

CPC (source: EP US)
B26D 7/32 (2013.01 - EP US); **B65H 29/242** (2013.01 - EP US); **B65H 31/00** (2013.01 - US); **B65H 35/00** (2013.01 - US); **B26D 2007/322** (2013.01 - EP US); **B42C 19/06** (2013.01 - EP US); **B65H 2301/42172** (2013.01 - EP); **B65H 2301/44512** (2013.01 - EP US); **B65H 2403/20** (2013.01 - EP US); **B65H 2404/252** (2013.01 - EP US); **B65H 2404/511** (2013.01 - EP US); **B65H 2406/32** (2013.01 - EP US); **B65H 2601/324** (2013.01 - EP); **B65H 2801/48** (2013.01 - EP US); **Y10T 83/207** (2015.04 - EP US)

Citation (search report)
See references of WO 2013160399A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2013160399 A1 20131031; BR 112014026504 A2 20170627; BR 112014026504 B1 20201208; CA 2870782 A1 20131031; CA 2870782 C 20200804; CL 2014002837 A1 20150410; CN 104718147 A 20150617; CN 104718147 B 20170801; DE 102012206847 A1 20131107; EP 2841365 A1 20150304; EP 2841365 B1 20180418; ES 2678212 T3 20180809; HK 1201803 A1 20150911; IN 9661DEN2014 A 20150807; JP 2015515386 A 20150528; JP 6062038 B2 20170118; MX 2014013077 A 20150511; US 11279583 B2 20220322; US 2015096415 A1 20150409; US 2020055687 A1 20200220

DOCDB simple family (application)
EP 2013058626 W 20130425; BR 112014026504 A 20130425; CA 2870782 A 20130425; CL 2014002837 A 20141021; CN 201380033729 A 20130425; DE 102012206847 A 20120425; EP 13718585 A 20130425; ES 13718585 T 20130425; HK 15102245 A 20150305; IN 9661DEN2014 A 20141117; JP 2015507534 A 20130425; MX 2014013077 A 20130425; US 201314397047 A 20130425; US 201916574973 A 20190918