

Title (en)

Laundry treating machine comprising a cover supported by a hinge

Title (de)

Wäschebehandlungsmaschine mit von einem Scharnier gehaltener Abdeckung

Title (fr)

Machine de traitement du linge avec un couvercle supporté par une charnière

Publication

EP 2843102 B1 20160720 (EN)

Application

EP 13182525 A 20130830

Priority

EP 13182525 A 20130830

Abstract (en)

[origin: EP2843102A1] The present invention relates to a laundry treating machine (1) comprising a casing (2) accommodating a laundry chamber (7) suitable for receiving laundry to be treated and a closing door (8) provided for allowing access to the chamber, said machine being provided with a cover (20) which is removably connected to said casing (2) by means of at least one hinge (30, 30') supporting said cover (20) in rotation around a rotation axis (X), so that it can swing between a closed position and an opened position around said rotation axis. Said hinge (30, 30') comprises at least two rotation pins (35, 36, 36') which, in a dismounted configuration of said cover (20), have respective distinct axes (Y, Z), and, in a mounted configuration of said cover (20), when they are coupled to at least two respective seats (37, 38, 38'), said at least two rotation pins (35, 36, 36') have said respective axes (Y, Z) moved closer than in said dismounted configuration of said cover (20).

IPC 8 full level

D06F 39/12 (2006.01); **D06F 39/14** (2006.01); **D06F 58/20** (2006.01); **E05D 7/10** (2006.01)

CPC (source: EP US)

D06F 39/12 (2013.01 - EP US); **D06F 39/14** (2013.01 - EP US); **E05D 7/1077** (2013.01 - EP); **E05D 2005/102** (2013.01 - EP);
E05Y 2800/22 (2013.01 - EP); **E05Y 2900/312** (2013.01 - EP)

Cited by

CN114269980A; CN105455485A; WO2021032586A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2843102 A1 20150304; EP 2843102 B1 20160720

DOCDB simple family (application)

EP 13182525 A 20130830