

Title (en)

SYSTEM FOR LAUNCHING AND RETRIEVING SUBMARINE VEHICLES, IN PARTICULAR TOWED SUBMARINE VEHICLES

Title (de)

SYSTEM ZUM STARTEN UND ZURÜCKHOLEN VON UNTERWASSERFAHRZEUGEN, INSBESONDERE GEZOGENEN UNTERWASSERFAHRZEUGEN

Title (fr)

SYSTEME DE MISE A L'EAU ET DE RECUPERATION D'ENGINS SOUS-MARINS, NOTAMMENT D'ENGINS SOUS-MARINS TRACTES

Publication

EP 2855252 B1 20160622 (FR)

Application

EP 13728697 A 20130531

Priority

- FR 1201573 A 20120601
- EP 2013061272 W 20130531

Abstract (en)

[origin: WO2013178792A1] The invention relates to a system for automatically launching and retrieving, with no human intervention, marine or submarine vehicles (15) from a carrier ship (10) which remains in movement in order to limit the amplitude of the pitch and roll movements to which the vehicle is subjected. The system comprises a tiltable hinged ramp (11) which comprises a bottom (113) and edges (114, 115), and a towing means (14, 16) making it possible to control the sliding of the vehicle (15) along the ramp (11) during the launch and to hoist the vehicle (15) along the ramp (11) during the retrieval thereof. The ramp has a free end (112), the vertical position of which varies between a submerged position, in which said end is immersed in the water, and an above-water position, in which the ramp is in horizontal position. The system also comprises a buoyancy means which enables the free end to float on or near the surface of the water when the ramp is lowered. The bottom of the hinged ramp also has an outer surface configured such as to form a dry dock having a V-shaped or W-shaped cross-section, and a receiving and guiding means (13) comprising a receiving device configured such as to receive the end of the vehicle and to remain in contact with the vehicle during the launch and retrieval operations, the receiving device being driven with the vehicle by the towing means. The receiving device comprises vertical protection elements (131) intended for providing a frontal bearing for wings of the vehicle when the end thereof is inserted in the receiving device, the frontal bearing thus provided making it possible to contribute to keeping the vehicle aligned with the ramp.

IPC 8 full level

B63B 21/66 (2006.01); **B63B 27/36** (2006.01); **B63B 27/14** (2006.01); **B63G 8/00** (2006.01); **B63G 8/42** (2006.01)

CPC (source: EP)

B63B 21/66 (2013.01); **B63B 27/36** (2013.01); **B63B 27/143** (2013.01); **B63G 8/001** (2013.01); **B63G 8/42** (2013.01); **B63G 2008/007** (2013.01)

Cited by

CN116002068A; CN110341915A; NO20200901A1; NO346852B1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

WO 2013178792 A1 20131205; AU 2013269527 A1 20150122; AU 2013269527 B2 20170105; CA 2875597 A1 20131205; CA 2875597 C 20190917; EP 2855252 A1 20150408; EP 2855252 B1 20160622; FR 2991284 A1 20131206; FR 2991284 B1 20150515; IN 11251DEN2014 A 20151009; SG 11201407997Q A 20150129

DOCDB simple family (application)

EP 2013061272 W 20130531; AU 2013269527 A 20130531; CA 2875597 A 20130531; EP 13728697 A 20130531; FR 1201573 A 20120601; IN 11251DEN2014 A 20141231; SG 11201407997Q A 20130531