

Title (en)

SILICON CARBIDE SEMICONDUCTOR DEVICE AND METHOD FOR PRODUCING SAME

Title (de)

SILICIUMCARBID-HALBLEITERBAUELEMENT UND VERFAHREN ZUR HERSTELLUNG DAVON

Title (fr)

DISPOSITIF SEMI-CONDUCTEUR AU CARBURE DE SILICIUM ET PROCÉDÉ DE FABRICATION DUDIT DISPOSITIF

Publication

EP 2863417 A4 20160309 (EN)

Application

EP 13804396 A 20130606

Priority

- JP 2012134917 A 20120614
- JP 2013003547 W 20130606

Abstract (en)

[origin: EP2863417A1] In a method for producing an SiC semiconductor device, a p type layer (31) is formed in a trench (6) by epitaxially growing, and is then left only on a bottom portion and ends of the trench by hydrogen etching, thereby to form a p type SiC layer (7). That is, a portion of the p type layer (31) formed on a side surface of the trench (6) is removed. Thus, the p type SiC layer (7) can be formed without depending on diagonal ion implantation. Since it is not necessary to separately perform the diagonal ion implantation, it is less likely that a production process will be complicated due to transferring into an ion implantation apparatus, and thus manufacturing costs reduce. Since there is no damage due to a defect caused by the ion implantation, it is possible to reduce a drain leakage and to reliably restrict the p type SiC layer (7) from remaining on the side surface of the trench (6). Accordingly, it is possible to produce an SiC semiconductor device that can achieve both high withstand voltage and high switching speed.

IPC 8 full level

H01L 21/336 (2006.01); **H01L 29/06** (2006.01); **H01L 29/12** (2006.01); **H01L 29/78** (2006.01)

CPC (source: CN EP US)

H01L 21/02529 (2013.01 - US); **H01L 21/0455** (2013.01 - US); **H01L 21/0475** (2013.01 - US); **H01L 21/049** (2013.01 - US); **H01L 21/3065** (2013.01 - EP US); **H01L 29/0623** (2013.01 - CN EP US); **H01L 29/1608** (2013.01 - CN EP US); **H01L 29/4236** (2013.01 - CN EP US); **H01L 29/66068** (2013.01 - CN EP US); **H01L 29/66348** (2013.01 - US); **H01L 29/66734** (2013.01 - US); **H01L 29/7397** (2013.01 - CN EP US); **H01L 29/7811** (2013.01 - CN EP US); **H01L 29/7813** (2013.01 - CN EP US); **H01L 29/7827** (2013.01 - US); **H01L 29/045** (2013.01 - CN EP US); **H01L 29/0619** (2013.01 - CN EP US); **H01L 29/0661** (2013.01 - CN EP US); **H01L 29/0696** (2013.01 - CN EP US); **H01L 29/1095** (2013.01 - CN EP US)

Citation (search report)

- [XY] US 2010224932 A1 20100909 - TAKAYA HIDEFUMI [JP], et al & JP 2007242852 A 20070920 - TOYOTA MOTOR CORP
- [Y] US 2008038890 A1 20080214 - TUCKER JESSE [US]
- [Y] US 2010006861 A1 20100114 - YAMAMOTO KENSAKU [JP], et al
- [Y] JP 2001267570 A 20010928 - MITSUBISHI ELECTRIC CORP
- [Y] US 2010019250 A1 20100128 - NAKAMURA SHUN-ICHI [JP], et al
- [A] US 2005233539 A1 20051020 - TAKEUCHI YUUICHI [JP], et al
- [A] US 2011018004 A1 20110127 - SHIMIZU HARUKA [JP], et al
- [A] US 6194741 B1 20010227 - KINZER DANIEL M [US], et al
- See references of WO 2013187019A1

Cited by

EP4113623A1; US10374081B2; US11563080B2; WO2017182864A1; WO2017145210A1; WO2021222180A1; US10367091B2; US10460931B2; WO2017097482A1; WO2017145211A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

EP 2863417 A1 20150422; EP 2863417 A4 20160309; EP 2863417 B1 20210310; CN 104380442 A 20150225; CN 104380442 B 20170531; JP 2013258369 A 20131226; JP 5751213 B2 20150722; KR 101662629 B1 20161005; KR 20150006888 A 20150119; US 2015129895 A1 20150514; US 2016163818 A1 20160609; US 9337298 B2 20160510; US 9515160 B2 20161206; WO 2013187019 A1 20131219

DOCDB simple family (application)

EP 13804396 A 20130606; CN 201380031331 A 20130606; JP 2012134917 A 20120614; JP 2013003547 W 20130606; KR 20147034621 A 20130606; US 201314402119 A 20130606; US 201615001726 A 20160120