

Title (en)  
LIGHTING SYSTEM WITH AN INTERFACE HAVING A POWER SUPPLY UNIT AND AT LEAST ONE LIGHT SOURCE MODULE

Title (de)  
BELEUCHTUNGSANLAGE MIT EINER SCHNITTSTELLE AUFWEISEND EIN NETZGERÄT UND MINDESTENS EIN LICHTQUELLENMODUL

Title (fr)  
SYSTÈME D'ÉCLAIRAGE ÉQUIPÉ D'UNE INTERFACE COMPRENANT UN BLOC D'ALIMENTATION ET AU MOINS UN MODULE DE SOURCES LUMINEUSES

Publication  
**EP 2865239 A1 20150429 (DE)**

Application  
**EP 13734701 A 20130625**

Priority  
• IT TO20120558 A 20120625  
• DE 102012224349 A 20121221  
• EP 2013063317 W 20130625

Abstract (en)  
[origin: WO2014001342A1] The invention relates to a power supply unit (PSU) having an output for outputting an operating current on the basis of an internal measurement signal, a communication line, a current measuring device which is connected to the communication line, wherein the current measuring device is set up to generate a current on the communication line, which current is proportional to the conductance of a current setting resistor, the current measuring device has a current mirror which is set up to mirror the generated current on the communication line, the current measuring device is set up to convert the mirrored current into an internal measurement signal having a reference potential different from the communication line, at least one light source module can be connected to the output, wherein the at least one light source module has the current setting resistor which can be connected to the communication line. The invention also relates to a light source module for connection to a power supply unit, wherein the light source module has an input and a communication line and a current setting resistor for setting the current applied to the light source module. The invention also relates to a lighting system having a power supply unit and at least one light source module. The invention also relates to a method for setting a current value for at least one light source module connected to a power supply unit, having the following steps of: -applying a measurement voltage to a communication line by means of a current mirror, mirroring the current flowing in the communication line, converting the mirrored current into an internal measurement signal having a reference potential different from the communication line, assessing the internal measurement signal, setting an operating current at the output of the power supply unit using the assessed measurement signal.

IPC 8 full level  
**H05B 44/00** (2022.01)

CPC (source: CN EP US)  
**H05B 45/10** (2020.01 - EP US); **H05B 45/14** (2020.01 - EP US); **H05B 45/37** (2020.01 - CN); **H05B 45/397** (2020.01 - EP);  
**H05B 45/40** (2020.01 - EP US); **H05B 45/46** (2020.01 - US); **H05B 45/56** (2020.01 - EP US); **Y02B 20/30** (2013.01 - EP)

Citation (search report)  
See references of WO 2014001360A1

Citation (examination)  
• WO 2011067177 A1 20110609 - OSRAM GMBH [DE], et al  
• DE 10051528 A1 20020502 - VOSSLOH SCHWABE ELEKTRONIK [DE]  
• WU CHEN ET AL: "A Dimmable Light-Emitting Diode (LED) Driver With Mag-Amp Postregulators for Multistring Applications", IEEE TRANSACTIONS ON POWER ELECTRONICS, INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS, USA, vol. 26, no. 6, 1 June 2011 (2011-06-01), pages 1714 - 1722, XP011382812, ISSN: 0885-8993, DOI: 10.1109/TPEL.2010.2082565  
• "Signal conditioning", 21 February 2012 (2012-02-21), Retrieved from the Internet <URL:https://en.wikipedia.org/wiki/Signal\_conditioning> [retrieved on 20180228]  
• "Sensor Signal Conditioning", 22 July 2012 (2012-07-22), Retrieved from the Internet <URL:http://ansari-electronics.com/signal\_conditioning/> [retrieved on 20180301]

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**DE 102012224348 A1 20140102**; CN 104412708 A 20150311; CN 104412708 B 20160907; CN 104412709 A 20150311; CN 104412709 B 20170322; CN 104412710 A 20150311; CN 104412710 B 20161109; CN 105960056 A 20160921; CN 105960056 B 20180209; DE 102012224349 A1 20140102; EP 2865238 A1 20150429; EP 2865238 B1 20200909; EP 2865239 A1 20150429; EP 2865240 A2 20150429; EP 2865240 B1 20201111; EP 3413690 A1 20181212; EP 3413690 A8 20190220; EP 3413690 B1 20201111; US 2015145437 A1 20150528; US 2015195877 A1 20150709; US 2015195884 A1 20150709; US 2017111966 A1 20170420; US 9445466 B2 20160913; US 9554430 B2 20170124; US 9609700 B2 20170328; US 9872350 B2 20180116; WO 2014001342 A1 20140103; WO 2014001360 A1 20140103; WO 2014001987 A2 20140103; WO 2014001987 A3 20140227

DOCDB simple family (application)  
**DE 102012224348 A 20121221**; CN 201380033923 A 20130621; CN 201380033977 A 20130625; CN 201380033982 A 20130625; CN 201610374688 A 20130621; DE 102012224349 A 20121221; EP 13732132 A 20130625; EP 13734701 A 20130625; EP 13765423 A 20130621; EP 18182484 A 20130621; EP 2013063293 W 20130625; EP 2013063317 W 20130625; IB 2013055106 W 20130621; US 201314408570 A 20130625; US 201314409479 A 20130621; US 201314410581 A 20130625; US 201715396837 A 20170103