

Title (en)

Method of using asymmetric corrugated fins with louvers

Title (de)

Verfahren zur Verwendung asymmetrisch gewellter Rippen mit Kiemen

Title (fr)

Méthode d'utilisation d'ailettes ondulées asymétriques avec des persiennes

Publication

EP 2869015 A1 20150506 (EN)

Application

EP 13191548 A 20131105

Priority

EP 13191548 A 20131105

Abstract (en)

A fluid flow guide member (16) of a heat exchanger (10), adapted to be traversed by a fluid flow (F). The guide member (16) is made from a corrugated metallic strip (18), the width (W) of which extends along a transversal axis (T) from a leading edge (26) to a trailing edge (28). The leading edge portion (30) of the guide member (16) is provided with slit louvers (34) adapted to deviate the flow (F) and, the trailing edge portion (32) is free of slit louvers.

IPC 8 full level

F28F 1/12 (2006.01)

CPC (source: EP)

F28F 1/128 (2013.01)

Citation (search report)

- [XY] EP 2657637 A1 20131030 - DAIKIN IND LTD [JP]
- [Y] AU 2012208120 A1 20130801 - DAIKIN IND LTD [JP]
- [X] JP H08178366 A 19960712 - SHARP KK
- [X] US 2007199686 A1 20070830 - OKINOTANI TAKESHI [JP], et al
- [X] JP H09280754 A 19971031 - SHOWA ALUMINUM CORP

Cited by

FR3100058A1; WO2021038152A1; WO2021014094A1; FR3099239A1; WO2021014092A1; FR3099240A1; WO2021014091A1; FR3099238A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

EP 2869015 A1 20150506; EP 2869015 B1 20170920

DOCDB simple family (application)

EP 13191548 A 20131105