

Title (en)

FILLING PUNCH STATION AND METHOD FOR FILLING CAPSULES IN A FILLING PUNCH STATION

Title (de)

STOPFSTEMPELSTATION UND VERFAHREN ZUM FÜLLEN VON KAPSELN IN EINER STOPFSTEMPELSTATION

Title (fr)

STATION À TIGE-POUSOIR ET PROCÉDÉ DE REMPLISSAGE DE CAPSULE DANS UNE STATION À TIGE-POUSOIR

Publication

**EP 2886099 A1 20150624 (DE)**

Application

**EP 14199660 A 20141222**

Priority

DE 102013114693 A 20131220

Abstract (en)

[origin: CN104721053A] A tamping punch station for filling capsules in a capsule filling machine is described. The machine includes a rotatably drivable dosing disk with bore holes and a filling device for filling the bore holes. Tamping punches and ejection punches are held on a punch support, and vertical movement of the punch support causes the tamping punches to press filling material into the bore holes and the ejection punches to eject pellets created by the tamping punches in the bore holes. First drive means rotates the dosing disk along punches and second drive means moves the punch support. The second drive means comprises at least two spindle drives acting on the punch support with respectively one spindle nut and respectively one vertical drive spindle guided in the spindle nut and at least two drive motors, which drive respectively one of the spindle drives for vertical movement of the punch support. The present invention also relates to a method for filling capsules in the tamping punch station.

Abstract (de)

Die Erfindung betrifft eine Stopfstempelstation zum Befüllen von Kapseln mit Füllmaterial in einer Kapselfüllmaschine, umfassend eine drehend antreibbare Dosierscheibe, die mindestens eine Gruppe von Bohrungen umfasst, eine Fülleinrichtung zum Befüllen der Bohrungen mit dem Füllmaterial, mindestens eine Gruppe von Stopfstempeln und eine Gruppe von Ausstoßstempeln, wobei die Stopfstempel und die Ausstoßstempel an einem vertikal verfahrbaren Stempelträger gehalten sind, wobei durch vertikales Verfahren des Stempelträgers die Stopfstempel zum Verpressen des Füllmaterials in die Bohrungen und die Ausstoßstempel zum Ausstoßen von durch die Stopfstempel in den Bohrungen erzeugten Presslingen in die Bohrungen einfahren können, wobei erste Antriebsmittel zum schrittweisen Drehen der Dosierscheibe entlang der mindestens einen Gruppe von Stopfstempeln und der Gruppe von Ausstoßstempeln und zweite Antriebsmittel zum vertikalen Verfahren des Stempelträgers vorgesehen sind, wobei die zweiten Antriebsmittel mindestens zwei auf den Stempelträger wirkende Spindeltriebe mit jeweils einer Spindelmutter und jeweils einer in der Spindelmutter geführten vertikalen Antriebsspindel umfassen, und wobei die zweiten Antriebsmittel mindestens zwei Antriebsmotoren umfassen, die jeweils einen der Spindeltriebe zum vertikalen Verfahren des Stempelträgers antreiben. Die Erfindung betrifft außerdem ein Verfahren zum Füllen von Kapseln einer Stopfstempelstation.

IPC 8 full level

**A61J 3/07** (2006.01); **B30B 1/18** (2006.01); **B30B 9/30** (2006.01)

CPC (source: EP KR US)

**A61J 3/07** (2013.01 - KR); **A61J 3/074** (2013.01 - EP KR US); **B30B 1/18** (2013.01 - EP US); **B30B 9/3064** (2013.01 - EP US); **B65B 1/04** (2013.01 - US); **B65B 63/026** (2013.01 - US)

Citation (applicant)

DE 102006014496 A1 20071004 - BOSCH GMBH ROBERT [DE]

Citation (search report)

- [Y] EP 1135294 A1 20010926 - IMA SPA [IT]
- [Y] DE 102012010767 A1 20131205 - FETTE COMPACTING GMBH [DE]

Cited by

CN109157417A; EP3085353B1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

**EP 2886099 A1 20150624**; **EP 2886099 B1 20160720**; CN 104721053 A 20150624; CN 104721053 B 20181102; DE 102013114693 A1 20150625; IN 4093MU2014 A 20151016; JP 2015119970 A 20150702; JP 6254515 B2 20171227; KR 101766694 B1 20170809; KR 20150073127 A 20150630; US 10569912 B2 20200225; US 2015175279 A1 20150625

DOCDB simple family (application)

**EP 14199660 A 20141222**; CN 201410858473 A 20141219; DE 102013114693 A 20131220; IN 4093MU2014 A 20141219; JP 2014257034 A 20141219; KR 20140186056 A 20141222; US 201414577278 A 20141219