

Title (en)
BALE OPENER

Title (de)
BALLENÖFFNER

Title (fr)
DISPOSITIF D'OUVERTURE DE BALLES

Publication
EP 2890840 A1 20150708 (DE)

Application
EP 13779908 A 20130816

Priority
• CH 15002012 A 20120829
• IB 2013001792 W 20130816

Abstract (en)
[origin: WO2014033518A1] The invention relates to a removal element (1) for removing fiber flocks from fiber bales (2), comprising a removal roller (3) having an axis (7) and having teeth (6), a suction hood (4) arranged over the removal roller (3), and a grille (5) arranged under the removal roller (3), through which grille the teeth (6) of the removal roller (3) reach. The removal element (1) is supported on a removal tower (8) on one side. The suction hood (4) is formed by a trapezoidal first part (10), which is put over the removal roller (3) and is open at the bottom and has a first angle of inclination (α) and a second angle of inclination (β), and an arcuate second part (11), which is arranged between the first part (10) and a transport channel (12) arranged in the removal tower (8). The first part (10) of the suction hood (4) is provided with leak-air openings (9) on the side facing away from the removal tower (8).

IPC 8 full level
D01G 7/12 (2006.01)

CPC (source: CN EP)
D01G 7/12 (2013.01 - CN EP)

Citation (search report)
See references of WO 2014033518A1

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
WO 2014033518 A1 20140306; CH 706899 A1 20140314; CN 104583476 A 20150429; CN 104583476 B 20170915; EP 2890840 A1 20150708; EP 2890840 B1 20161005

DOCDB simple family (application)
IB 2013001792 W 20130816; CH 15002012 A 20120829; CN 201380045027 A 20130816; EP 13779908 A 20130816