

Title (en)

INSULATION FLUID FILLING METHOD AND FILLING APPARATUS

Title (de)

FÜLLVERFAHREN UND FÜLLVORRICHTUNG FÜR EINE ISOLIERFLÜSSIGKEIT

Title (fr)

PROCÉDÉ DE REMPLISSAGE AVEC DU FLUIDE D'ISOLATION ET APPAREIL DE REMPLISSAGE

Publication

EP 2893544 A1 20150715 (EN)

Application

EP 13759713 A 20130904

Priority

- EP 2012067222 W 20120904
- EP 13172590 A 20130619
- EP 2013068278 W 20130904
- EP 13759713 A 20130904

Abstract (en)

[origin: WO2014037396A1] A method and device for providing an insulation fluid (10) and for filling this insulation fluid (10) into medium-voltage or high-voltage switchgear (1) is provided. The method comprises method elements of mixing at least two fluid components (A,B) for yielding a first amount (M1) of insulation fluid (10), monitoring a first mixing ratio (R1) of this first amount (M1), and monitoring a second mixing ratio (R2) of a second amount (M2) of the insulation fluid (10) that is already in the electrical apparatus (1). The first mixing ratio (R1) is controlled such that no condensation of a fluid component (A,B) takes place. Furthermore, the first mixing ratio (R1) and the first amount (M1) of the insulation fluid are controlled using the second mixing ratio (R2), the second amount (M2), a desired target mixing ratio (R), and a target amount (M) of the insulation fluid.

IPC 8 full level

H01H 33/22 (2006.01); **H01B 3/56** (2006.01); **H01H 33/56** (2006.01); **H02B 13/055** (2006.01)

CPC (source: EP)

H01B 3/56 (2013.01); **H01H 33/22** (2013.01); **H01H 33/563** (2013.01)

Citation (search report)

See references of WO 2014037396A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2014037396 A1 20140313; EP 2893544 A1 20150715

DOCDB simple family (application)

EP 2013068278 W 20130904; EP 13759713 A 20130904