

Title (en)  
HOLDER ARRANGEMENT FOR GRINDING TOOLS

Title (de)  
HALTEANORDNUNG FÜR SCHLEIFWERKZEUGE

Title (fr)  
AGENCEMENT DE SUPPORT POUR AFFÛTER DES OUTILS

Publication  
**EP 2903781 A4 20160601 (EN)**

Application  
**EP 13843962 A 20131004**

Priority  
• SE 1251129 A 20121005  
• SE 2013051170 W 20131004

Abstract (en)  
[origin: WO2014055031A1] The invention relates to an arrangement (1) at rotatable disc-shaped holder (2) for grinding tools comprising grinding segments (3), which can be releasably attached in radially (4) directed tapering grooves (5) in the holder (2) in question. A number of magnets (6) are arranged between the holder (2) and the grinding segments (3) in question in order to hold the respective grinding segments (3) in intended working position (I), in which they are intended to be held. Said number of magnets (6) in question is/are arranged to form obstacles to the grinding segments (3) and hold the grinding segments (3) in the intended holding positions (I).

IPC 8 full level  
**B24B 7/18** (2006.01); **B24D 7/06** (2006.01)

CPC (source: EP SE)  
**B24B 7/186** (2013.01 - EP SE); **B24D 7/066** (2013.01 - EP SE)

Citation (search report)  
• [A] CN 201309125 Y 20090916 - ADVANCED TECHNOLOGY & MATERIAL [CN]  
• [A] WO 2007011289 A1 20070125 - SCANMASKIN SVERIGE AB [SE], et al  
• [A] WO 2011008077 A1 20110120 - BLASTRAC B V [NL], et al  
• [A] CH 523746 A 19720615 - MARRA DONATO [CH]  
• [A] WO 2011074773 A2 20110623 - SUNGSIM CO LTD [KR], et al  
• [A] KR 20110116640 A 20111026 - DIATOP SAMA CO LTD [KR]  
• See references of WO 2014055031A1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)  
**WO 2014055031 A1 20140410**; EP 2903781 A1 20150812; EP 2903781 A4 20160601; EP 2903781 B1 20170628; SE 1251129 A1 20140406; SE 537919 C2 20151124

DOCDB simple family (application)  
**SE 2013051170 W 20131004**; EP 13843962 A 20131004; SE 1251129 A 20121005