

Title (en)
FITTING FOR A VEHICLE SEAT AND VEHICLE SEAT

Title (de)
BESCHLAG FÜR EINEN FAHRZEUGSITZ UND FAHRZEUGSITZ

Title (fr)
FERRURE POUR SIÈGE DE VÉHICULE ET SIÈGE DE VÉHICULE

Publication
EP 2903855 B1 20160817 (DE)

Application
EP 13770479 A 20130927

Priority
• DE 102012019698 A 20121004
• DE 102012023057 A 20121122
• EP 2013070151 W 20130927

Abstract (en)
[origin: WO2014053400A1] The invention relates to a fitting (10) for a vehicle seat (1) having • a) a first fitting part (11) and a second fitting part (12), which can be rotated relative to one another around an axis (A), wherein a sprocket (17) is formed on the first fitting part (11) and guide segments (14) are formed on the second fitting part (12), • b) at least one bar (16), which can be guided in a radially displaceable manner by means of the guide segments (14) between a locked state and an unlocked state, and which interacts with the sprocket (17) in the locked state, in order to lock the fitting (10), the at least one bar (16) having a first bar cam (16a) and a second bar cam (16b), and • c) an eccentric (27) which is rotatably mounted around the axis (A), and which, by rotating in a closing direction (c) in the transition from the unlocked state to the locked state, strikes the bar (16) with a force for clamping the bar (16) against the sprocket (17), wherein the eccentric (27) has, for striking the bar (16), a first eccentric cam (28, 128), which is suitable for interacting with the first bar cam (16a), and a second eccentric cam (29, 129), which is suitable for interacting with the second bar cam (16b). According to the invention • d) the first eccentric cam (28, 128) has a cam section (28.2) which runs in the peripheral direction concentrically around the axis A and • e) the cam section (28.2) running concentrically round the axis (A) is arranged upstream in the closing direction (c) of a further cam section (28.4) of the first eccentric cam (28, 128), and the further cam section (28.4) has a cam contour running radially outwards downstream in the closing direction (c) relative to the concentrically peripheral contour for clamping the bar (16) against the sprocket (17).

IPC 8 full level
B60N 2/235 (2006.01); **B60N 2/90** (2018.01)

CPC (source: CN EP KR US)
B60N 2/20 (2013.01 - US); **B60N 2/22** (2013.01 - CN); **B60N 2/235** (2013.01 - CN); **B60N 2/2356** (2013.01 - KR US); **B60N 2/236** (2015.04 - EP US); **B60N 2/235** (2013.01 - US)

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)
WO 2014053400 A1 20140410; CN 104520141 A 20150415; CN 104520141 B 20180105; DE 102012023057 A1 20140424; DE 102012023057 B4 20201119; EP 2903855 A1 20150812; EP 2903855 B1 20160817; IN 10799DEN2014 A 20150904; JP 2015523280 A 20150813; JP 5933840 B2 20160615; KR 101655133 B1 20160907; KR 20150034241 A 20150402; PL 2903855 T3 20170228; US 2015298585 A1 20151022; US 9481270 B2 20161101

DOCDB simple family (application)
EP 2013070151 W 20130927; CN 201380041484 A 20130927; DE 102012023057 A 20121122; EP 13770479 A 20130927; IN 10799DEN2014 A 20141217; JP 2015524813 A 20130927; KR 20157003090 A 20130927; PL 13770479 T 20130927; US 201314417940 A 20130927