

Title (en)  
DEVICE FOR GENERATING A RELIABLE LOW-IMPEDANCE ELECTRIC SHORT-CIRCUIT IRRESPECTIVELY OF THE OPERATING VOLTAGE

Title (de)  
EINRICHTUNG ZUM BETRIEBSSPANNUNGSUNABHÄNGIGEN ERZEUGEN EINES SICHEREN, NIEDEROHMIGEN ELEKTRISCHEN KURZSCHLUSSES

Title (fr)  
DISPOSITIF POUR PRODUIRE UN COURT-CIRCUIT ÉLECTRIQUE HAUTE IMPÉDANCE, SÛR, INDÉPENDAMMENT DE LA TENSION DE FONCTIONNEMENT

Publication  
**EP 2915178 A1 20150909 (DE)**

Application  
**EP 13752905 A 20130827**

Priority  
• DE 102012021384 A 20121031  
• DE 102013005783 A 20130404  
• EP 2013067689 W 20130827

Abstract (en)  
[origin: WO2014067691A1] The invention relates to a device for generating a reliable low-impedance electric short-circuit irrespectively of the operating voltage, comprising two electric connection parts (1, 2) which are plate-shaped in particular and which carry a different potential. An insulating section is formed between the connection parts, and the desired short-circuit is implemented by at least partly penetrating or destroying the insulating section. According to the invention, the connection parts are arranged closely adjacent to each other with the inclusion of the insulating section, and the insulating section is in the form of an insulating foil (4) or a foil-like coating. Furthermore, an exothermic mass (3) is located in the direct vicinity of the insulating section, and the mass releases exothermic energy when energy is applied and produces a melting or deformation of the insulating section such that the galvanic isolation between the connection parts (1, 2) is removed and the short-circuit event occurs.

IPC 8 full level  
**H01H 39/00** (2006.01); **H01T 1/14** (2006.01)

CPC (source: CN EP)  
**H01H 39/006** (2013.01 - CN EP); **H01T 1/14** (2013.01 - CN EP); **H01T 4/02** (2013.01 - CN EP)

Citation (search report)  
See references of WO 2014067691A1

Designated contracting state (EPC)  
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)  
BA ME

DOCDB simple family (publication)  
**DE 102013005783 A1 20140430; DE 102013005783 B4 20190613**; CN 104919560 A 20150916; CN 104919560 B 20170825; EP 2915178 A1 20150909; EP 2915178 B1 20170503; SI 2915178 T1 20170831; WO 2014067691 A1 20140508

DOCDB simple family (application)  
**DE 102013005783 A 20130404**; CN 201380057492 A 20130827; EP 13752905 A 20130827; EP 2013067689 W 20130827; SI 201330699 T 20130827