

Title (en)

SPRING CONTROL DEVICE FOR A CIRCUIT BREAKER

Title (de)

FEDERSTEUERUNGSVORRICHTUNG FÜR EINEN SCHUTZSCHALTER

Title (fr)

DISPOSITIF DE COMMANDE A RESSORT POUR UN DISJONCTEUR

Publication

EP 2923367 B1 20160824 (FR)

Application

EP 13792691 A 20131120

Priority

- FR 1261083 A 20121121
- EP 2013074274 W 20131120

Abstract (en)

[origin: WO2014079877A1] The control device according to the invention can be used to very quickly activate the opening of the circuit breakers used in medium- and high-voltage networks. The spring used in the control device is a composite spring, in a curved C or Ω shape. The spring (1) has a first fixed end (2) and a second mobile end (3) that is pivotably connected with the end of a lever device (7), which is itself constrained to rotate with the drive shaft (6) of the control device. Application to medium- and high-voltage circuit breakers.

IPC 8 full level

H01H 3/30 (2006.01); **H01H 3/38** (2006.01); **H01H 71/10** (2006.01)

CPC (source: CN EP US)

H01H 3/30 (2013.01 - EP US); **H01H 3/3015** (2013.01 - US); **H01H 3/38** (2013.01 - CN EP US); **H01H 3/46** (2013.01 - US); **H01H 5/18** (2013.01 - CN); **H01H 9/02** (2013.01 - US); **H01H 71/10** (2013.01 - CN EP US); **H01H 2235/018** (2013.01 - US)

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

DOCDB simple family (publication)

FR 2998413 A1 20140523; **FR 2998413 B1 20160205**; CN 104798159 A 20150722; CN 104798159 B 20170704; EP 2923367 A1 20150930; EP 2923367 B1 20160824; JP 2015535644 A 20151214; JP 6209221 B2 20171004; US 2015348718 A1 20151203; US 9589744 B2 20170307; WO 2014079877 A1 20140530

DOCDB simple family (application)

FR 1261083 A 20121121; CN 201380060934 A 20131120; EP 13792691 A 20131120; EP 2013074274 W 20131120; JP 2015542311 A 20131120; US 201314443283 A 20131120