

Title (en)

FLAME-RETARDANT POLYCARBONATE MOLDING MATERIALS I

Title (de)

FLAMMGESCHÜTZTE POLYCARBONATFORMMASSEN I

Title (fr)

MATIÈRES MOULABLES À BASE DE POLYCARBONATE IGNIFUGÉES I

Publication

EP 2928952 A1 20151014 (DE)

Application

EP 13798688 A 20131203

Priority

- EP 12196049 A 20121207
- EP 2013075314 W 20131203
- EP 13798688 A 20131203

Abstract (en)

[origin: WO2014086743A1] The invention relates to flame-retardant, impact-modified, high-temperature-stable polycarbonate (PC)-ABS compositions and molding materials that have a high modulus of elasticity, good flowability, and high hydrolysis stability, containing: A) 55 - 95 parts by weight of aromatic polycarbonate and/or aromatic polyester carbonate, B) 1.0 - 20.0 parts by weight of rubber-modified graft polymer, C) 1.0 - 20.0 parts by weight of at least one cyclic phosphazene according to formula (X), wherein k stands for 1 or an integer number from 1 to 10, preferably for a number from 1 to 8, especially preferably 1 to 5, wherein the trimer portion ($k=1$) is 60 to 98 mol % with respect to component C and wherein each R is the same or different and stands for an amine group, C1 to C8 alkyl, preferably methyl, ethyl, propyl, or butyl, which is optionally halogenated, preferably halogenated with fluorine, C1 to C8 alkoxy, preferably methoxy, ethoxy, propoxy, or butoxy, C5 to C6 cycloalkyl, which is optionally substituted with alkyl, preferably with C1 to C4 alkyl, and/or with halogen, preferably chlorine and/or bromine, C6 to C20 aryloxy, preferably phenoxy or naphthoxy, which is optionally substituted with alkyl, preferably with C1 to C4 alkyl, and/or with halogen, preferably with chlorine or bromine, and/or with hydroxy, C7 to C12 aralkyl, which is optionally substituted with alkyl, preferably with C1 to C4 alkyl, and/or with halogen, preferably with chlorine and/or bromine, preferably phenyl C1 to C4 alkyl, or a halogen group, preferably chlorine, or an OH group, D) 0 - 15 parts by weight of rubber-free vinyl (co)polymer or polyalkylene terephthalate, E) 0 - 15 parts by weight of additives, F) 0.05 - 5.0 parts by weight of anti-dripping agent, wherein all specifications of parts by weight are normalized in such a way that the sum of the parts by weight of all components A+B+C+D+E+F in the composition is 100. The invention further relates to the use of the compositions to produce molded bodies and the molded bodies produced from the compositions.

IPC 8 full level

C08K 5/5399 (2006.01); **C08L 55/02** (2006.01); **C08L 69/00** (2006.01)

CPC (source: EP US)

C07F 9/659 (2013.01 - US); **C08K 5/5399** (2013.01 - EP US); **C08L 27/18** (2013.01 - EP US); **C08L 69/00** (2013.01 - EP US); **C08L 55/02** (2013.01 - EP US); **C08L 2201/02** (2013.01 - US); **C08L 2205/025** (2013.01 - EP US); **C08L 2205/03** (2013.01 - US)

Citation (search report)

See references of WO 2014086743A1

Designated contracting state (EPC)

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)

BA ME

DOCDB simple family (publication)

WO 2014086743 A1 20140612; BR 112015012242 A2 20170711; CA 2893886 A1 20140612; CN 104822754 A 20150805; EP 2928952 A1 20151014; JP 2016501298 A 20160118; JP 6396312 B2 20180926; KR 102135991 B1 20200720; KR 20150093746 A 20150818; MX 2015007083 A 20150928; TW 201434961 A 20140916; TW I648339 B 20190121; US 2015315381 A1 20151105

DOCDB simple family (application)

EP 2013075314 W 20131203; BR 112015012242 A 20131203; CA 2893886 A 20131203; CN 201380063870 A 20131203; EP 13798688 A 20131203; JP 2015545774 A 20131203; KR 20157017746 A 20131203; MX 2015007083 A 20131203; TW 102144743 A 20131206; US 201314649047 A 20131203