

Title (en)
Multi-level power converter

Title (de)
Mehrstufiger Leistungswandler

Title (fr)
Convertisseur de puissance multi-niveaux

Publication
EP 2937985 A2 20151028 (FR)

Application
EP 15157308 A 20150303

Priority
FR 1452963 A 20140403

Abstract (en)
[origin: US2015288284A1] This is a multi-level converter comprising one or more arms (B) to each be connected between a voltage source (VDC) and a current source (I). Each arm comprises two stages (E1, E2) in cascade, the first to be connected to the voltage source (VDC), the second to be connected to the current source (I). The first stage (Et1) comprises several elementary stages (E1n, . . . , E12, E11) of rank one to n in cascade, the elementary stage (E11) of rank one being connected to the second stage (Et2) and the elementary stage (E1n) of rank n having to be connected to the voltage source (VDC). Each elementary stage (E1n) comprises a pair of identical cells of NPC type (Cen1, Cen2) in series, the connection being direct in the elementary stage of rank 1, the connection being made via n-1 capacitive cells ((Can(1), . . . Can(n-1)) for each elementary stage of rank greater than one, the second stage (Et2) comprising a floating capacitor cell (Ce10).

Abstract (fr)
Il s'agit d'un convertisseur multi-niveaux comportant un ou plusieurs bras (B) à connecter chacun entre une source de tension (VDC) et une source de courant (I). Chaque bras comprend deux étages (E1, E2) en cascade, le premier à connecter à la source de tension (VDC), le second à connecter à la source de courant (I). Le premier étage (Et1) comporte plusieurs étages élémentaires (E1n, ...E12, E11) de rang un à n en cascade, l'étage élémentaire (E11) de rang un étant connecté au second étage (Et2) et l'étage élémentaire (E1n) de rang n devant être connecté à la source de tension (VDC). Chaque étage élémentaire (E1n) comporte une paire de cellules de type NPC (Cen1, Cen2) identiques en série, la connexion étant directe dans l'étage élémentaire de rang 1, la connexion se faisant via n-1 cellules capacitives ((Can(1), ... Can(n-1)) pour chaque étage élémentaire de rang supérieur à un, le second étage (Et2) comportant une cellule à condensateur flottant (Ce10).

IPC 8 full level
H02M 7/487 (2007.01); **H02M 3/158** (2006.01); **H02M 5/42** (2006.01)

CPC (source: EP US)
H02M 3/158 (2013.01 - US); **H02M 5/42** (2013.01 - US); **H02M 7/4837** (2021.05 - EP); **H02M 7/487** (2013.01 - EP US);
H02M 1/007 (2021.05 - EP US); **H02M 1/0095** (2021.05 - EP)

Citation (applicant)
US 2007025126 A1 20070201 - BARBOSA PETER [CH], et al

Cited by
CN107528472A

Designated contracting state (EPC)
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated extension state (EPC)
BA ME

DOCDB simple family (publication)
EP 2937985 A2 20151028; EP 2937985 A3 20160120; EP 2937985 B1 20161228; AU 2015201700 A1 20151022; AU 2015201700 B2 20160421;
BR 102015006743 A2 20151208; BR 102015006743 B1 20220125; CN 104980054 A 20151014; CN 104980054 B 20180413;
ES 2619657 T3 20170626; FR 3019699 A1 20151009; FR 3019699 B1 20160513; RU 2593393 C1 20160810; US 2015288284 A1 20151008;
US 9553516 B2 20170124

DOCDB simple family (application)
EP 15157308 A 20150303; AU 2015201700 A 20150402; BR 102015006743 A 20150326; CN 201510151699 A 20150401;
ES 15157308 T 20150303; FR 1452963 A 20140403; RU 2015111900 A 20150401; US 201514635337 A 20150302